FITTINGS

GALAXY® 4826

Tube - CR | Barrier - PA | Friction - NBR | Reinforcement - PET | Friction - SBR | Cover - CIIR

- Two polyester spiral barrier hose
- J51 all outside diameters
- Temperature range -30°C 125°C
- \bullet Compatible with R-12 / R134a refrigerants and mineral oil / PAG's
- Meets J2064 "TYPE C Class II" hose performance
- Flexible easy to route

GOODYEAR BARRIER HOSE - 4826								
Part No	Hose Size	Length	Insid	le Dia.	Outside Dia.			
A15-5000	#6	Per Meter	5/	′16"	3/4"			
A15-5000/5	#6	5 Meters	GOOD FYEAR	/16"	3/4"			
A15-5000/10	#6	10 Meters		/16"	3/4"			
A15-5001	#8	Per Meter	CR PA NBR PET SBR PET EFDM	/32"	15/16"			
A15-5001/5	#8	5 Meters	13.	/32"	15/16"			
A15-5001/10	#8	10 Meters	13.	/32"	15/16"			
A15-5002	#10	Per Meter	ALCIUS 1.	/2"	1"			
A15-5002/5	#10	5 Meters	1.	/2"	1"			
A15-5002/10	#10	10 Meters	1.	/2"	1"			
A15-5003	#12	Per Meter	5.	/8"	1 1/8"			
A15-5003/5	#12	5 Meters	5.	/8"	1 1/8"			
A15-5003/10	#12	10 Meters	5,	/8"	1 1/8"			

ATCO		FEMALE FLARE		
Part No	Fitting Size		Hose Size	Thread Type
A03-ST-1101	#6	2009	#6	5/8" - 18
A03-ST-1103	#10		#10	7/8" - 14
A03-ST-1111	#6		#6	5/8" - 18
A03-ST-1112	#8		#8	3/4" - 16
A03-ST-1113	#10		#10	7/8" - 14
A03-ST-1121	#6	RICO PAR DATE CASE	#6	5/8" - 18
A03-ST-1123	#10		#10	7/8" - 14



Steel Barb