

SINGLE PACK

LV
automotive™

12 OR 24
VOLT

BATTERY CHARGERS

All models are compatible with Lead Acid, Gel, AGM & Lithium batteries & feature a minimum of 2 charging outputs.

They are ideal for fixed mount installation in motor homes, caravans & boats. Install the unit, set the charging algorithm required & let the charger go to work.

- Universal AC input with active PFC
- RS-232 communication interface
- Protection features: Short circuit protection, battery over voltage protection, over temperature shutdown, black-out protection
- 2 Stage fan speed control
- Dry contact for alarm
- High efficiency & high reliability
- Compatible with Lead Acid, Li-ion, Gel & AGM Batteries
- Built in battery rescue function & Engine Start Battery (ESB) output function
- Withstands 2G vibration test
- Output power OK signal
- Optional remote control - **LV1858** (suits LV1851-1857 with 25" cable)



LV1858



PRODUCT INFORMATION

Part No.	Input Voltage	Output voltage	Amperage	Output Port	Dimensions	Weight
LV1851	240Vac	12Vdc	25A (max)	2	183 x 72 x 243mm	1.7kg
LV1852	240Vac	12Vdc	35A (max)	2	183 x 72 x 263mm	1.9kg
LV1853	240Vac	12Vdc	50A (max)	3	213 x 77 x 272mm	3.1kg
LV1854	240Vac	12Vdc	80A (max)	3	213 x 77 x 312mm	4.0kg
LV1855	240Vac	24Vdc	12.5A (max)	2	183 x 72 x 263mm	1.6kg
LV1856	240Vac	24Vdc	25A (max)	3	213 x 77 x 272mm	2.9kg
LV1857	240Vac	24Vdc	40A (max)	3	213 x 77 x 312mm	3.9kg

INTELLI-CHARGE BATTERY CHARGERS

- 7 Stage charging
- Multi-chemistry
- Adjustable output
- Power supply mode
- Wired remote control
- Types: Wet, Calcium, AGM, Gel, Lithium
- Approvals electrical safety, EMC
- 5 Year warranty

12 VOLT
5 YEAR WARRANTY

PROJECTA



PRODUCT INFORMATION

Part No.	Input	Output	Output Current	Dimensions
IC15	240VAC, 50Hz, 240W	12V	2, 4, 8, 15A	222 x 108 x 61mm
IC25	240VAC, 50Hz, 450W	12V	2, 6, 12, 25A	210 x 108 x 61mm
IC35	240VAC, 50Hz, 570W	12V	2, 8, 16, 35A	250 x 108 x 61mm
IC50	240VAC, 50Hz, 800W	12V	2, 6, 12, 25, 50A	270 x 108 x 61mm