

SURFACE MOUNT SOCKETS & GAUGES

SINGLE PACK



LV1782H

DUAL SURFACE MOUNT TWIN OUTPUT USB PORT



- Twin USB Port x 2
- Voltage: 12/24V
- Current output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1732

DUAL SURFACE MOUNT ACCESSORY/ENGEL SOCKETS



- Accessory socket x 1 & engel socket x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1745

DUAL SURFACE MOUNT ACCESSORY/MERIT SOCKETS



- Accessory socket x 1 & merit socket x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1783

DUAL SURFACE MOUNT ACCESSORY SOCKET/VOLTMETER



- Accessory socket x 1 & voltmeter x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Voltmeter reading: 5-30V
- Voltmeter: Red LED display
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm



LV1783W

WHITE DUAL SURFACE MOUNT ACCESSORY SOCKET/VOLTMETER



- Accessory socket x 1 & voltmeter x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- Voltmeter reading: 5-30V
- Voltmeter: Red LED display
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm
- Marine applications



LV1781

DUAL SURFACE MOUNT ACCESSORY SOCKET/TWIN OUTPUT USB PORT



- Accessory socket x 1 & twin USB port x 1
- Voltage: 12/24V
- Current rating: 20A@12V
- USB output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 98(W) x 50(H) x 80(D)mm
- Cnt to cnt: 81.2mm

