

REVERSE CAMERA MONITORS

SINGLE PACK



LV7160 5.6" COLOUR MONITOR



- Voltage: 12/24V
- Screen: 5.6" full colour LCD monitor
- Built-in control module with twin camera input
- independent trigger wires for each camera
- Built-in microphone
- Automatic adjust day/night sensor
- Mirror function - invert screen
- Resolution: 4:3 (224,640 pixels)
- Operating temperature: -20°C to +70°C
- Dimensions: 164 x 115 x 29mm
- Camera to suit: **LV7172**



LV7161 7" COLOUR MONITOR



- Voltage: 12/24V
- Screen: 7" full colour LCD monitor
- Built-in control module with twin camera input
- independent trigger wires for each camera
- Built-in microphone
- Automatic adjust day/night sensor
- Mirror function - invert screen
- Resolution: 16:9 (336,960 pixels)
- Operating temperature: -20°C to +70°C
- Dimensions: 200 x 115 x 29mm
- Camera to suit: **LV7172**



LV7162 7" COLOUR MONITOR QUAD VIEW SCREEN BUILT IN CONTROL BOX



- Voltage: 12/24V
- Screen: 7" TFT full colour LCD monitor
- Built-in control module, quad (4) camera input
- Built-in speaker, multi language OSD display
- Colour system - PAL/NTSC
- Day/night mode
- Mirror function - invert screen
- Camera select override
- Voltage spike & short circuit protection
- Resolution: 16:9 (800 x 480 pixels)
- Operating temperature: -20°C to +70°C
- Dimensions: 200 x 138.5 x 76mm
- Camera to suit: **LV7172**

