

SURFACE MOUNT SOCKETS & GAUGES

SINGLE PACK



LV1743

SURFACE MOUNT MERIT SOCKET BLUE LED BACKLIGHT

- Voltage: 12/24V
- Current rating: 20A@12V
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm



LV1777

SURFACE MOUNT DIGITAL VOLTMETER

- Voltage: 12/24V
- Voltmeter reading: 5-30V
- Material: Thermoplastic Nylon 66
- Red LED display
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm



LV1777W

WHITE SURFACE MOUNT DIGITAL VOLTMETER

- Voltage: 12/24V
- Voltmeter reading: 5-30V
- Material: Thermoplastic Nylon 66
- Red LED display
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 40.8mm
- Marine applications



LV1794

SURFACE MOUNT DUAL DIGITAL VOLTMETER FOR MAIN & AUX. BATTERIES

- Voltage: 6 - 60V
- Voltmeter reading: 5 - 60V
- Material: Thermoplastic Nylon 66
- Blue LED display
- Terminals: Push on (3 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 41.3mm



LV1776H

SURFACE MOUNT TWIN OUTPUT USB PORT

- Voltage: 12/24V
- Current output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 41.3mm



LV1776W

WHITE SURFACE MOUNT TWIN OUTPUT USB PORT

- Voltage: 12/24V
- Current output: 5V/2.1A x 2
- Material: Thermoplastic Nylon 66
- Terminals: Push on (2 x 6.3mm)
- Dimensions: 55(W) x 50(H) x 80(D)mm
- Cnt to cnt: 41.3mm
- Marine applications

