

12V & 24V MICRO RELAYS





SINGLE PACK



LV4510

12V/25A 4 PIN MICRO RELAY
SPST N/O CIRCUIT


- Voltage: 12V
- Amperage: 25A
- Silver contacts
- Coil current: 97mA
- Coil resistance: 125 Ohms
- Operating temperature: -40°C to +125°C
- Protection: Resistor
- Terminal size: 2.8(W) x 0.8(T) x 11(L)mm
- No. of pins: 4



LV4519

12V/20A 4 PIN MICRO RELAY
SPST N/O CIRCUIT




- Voltage: 12V
- Amperage: 20A
- Silver contacts
- Coil current: 98mA
- Coil resistance: 135 Ohms
- Operating temperature: -40°C to +125°C
- Protection: Resistor
- Terminal size: 2.8(W) x 0.8(T) x 11(L)mm
- No. of pins: 4



LV4512

12V 30/20A 5 PIN CHANGEOVER
MICRO RELAY
SPDT N/O N/C CIRCUITS


- Voltage: 12V
- Amperage: 30/20A
- Silver contacts
- Coil current: 97mA
- Coil resistance: 125 Ohms
- Operating temperature: -40°C to +125°C
- Terminal size: 2.8(W) x 0.8(T) x 11(L)mm
- No. of pins: 5



LV4511

24V/15A 4 PIN MICRO RELAY
SPST N/O CIRCUIT

- Voltage: 24V
- Amperage: 15A
- Silver contacts
- Coil current: 47mA
- Coil resistance: 480 Ohms
- Operating temperature: -40°C to +125°C
- Protection: Resistor
- Terminal size: 2.8(W) x 0.8(T) x 11(L)mm
- No. of pins: 4



LV4513

24V 10/20A 5 PIN CHANGEOVER
MICRO RELAY
SPDT N/O N/C CIRCUITS

- Voltage: 24V
- Amperage: 10/20A
- Silver contacts
- Coil current: 47mA
- Coil resistance: 480 Ohms
- Operating temperature: -40°C to +125°C
- Terminal size: 2.8(W) x 0.8(T) x 11(L)mm
- No. of pins: 5

