

## MICRO SWITCHES

SINGLE PACK


**Britax**

### SMJ2-1307BP

MICRO SWITCH LARGE PUSH BUTTON  
MOMENTARY CONTACTS



- Material: Plastic
- Position: On/Off SPDT, 1x N/O, 1x N/C  
3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 250g - 450g
- Releasing force (RF): 114g Min
- Pre-travel (PT): 0.5mm Max
- Over travel (OT): 5.5mm Min
- Travel differential (DT): 0.05mm Max
- Operating position (OP): 38.1 ± 0.8mm




### SMJ2-1308BP

MICRO SWITCH PUSH ROLLER BUTTON  
MOMENTARY CONTACTS



- Material: Plastic, metal roller
- Position: On/Off, SPDT, 1x N/O, 1x N/C  
3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 250g - 450g
- Releasing force (RF): 114g Min
- Pre-travel (PT): 0.5mm Max
- Over travel (OT): 3.58mm Min
- Travel differential (DT): 0.05mm Max
- Operating position (OP): 49.7 ± 1.2mm




### SMJ2-1308RPBP

MICRO SWITCH PUSH ROLLER BUTTON  
MOMENTARY CONTACTS



- Material: Plastic, plastic roller
- Position: On/Off, SPDT, 1x N/O, 1x N/C  
3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 250g - 450g
- Releasing force (RF): 114g Min
- Pre-travel (PT): 0.5mm Max
- Over travel (OT): 5.5mm Min
- Travel differential (DT): 0.05mm Max
- Operating position (OP): 49.7 ± 1.2mm




### SMJ2-1515BP

MICRO SWITCH MEDIUM PUSH  
BUTTON MOMENTARY CONTACTS



- Material: Plastic
- Position: On/Off, SPDT, 1x N/O, 1x N/C  
3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 540g
- Releasing force (RF): 114g Min
- Pre-travel (PT): 2.3mm Max
- Over travel (OT): 1.6mm Min
- Travel differential (DT): 0.06mm Max
- Operating position (OP): 28.2 ± 0.5mm




### SMJ2-1701BP

MICRO SWITCH MEDIUM ARM  
BUTTON MOMENTARY CONTACTS



- Material: Plastic, metal arm
- Position: On/Off, SPDT, 1x N/O, 1x N/C  
3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 70g
- Releasing force (RF): 14g Min
- Pre-travel (PT): 10mm Max
- Over travel (OT): 5.6mm Min
- Travel differential (DT): 1.27mm Max
- Free position (FP): 28.2mm Max
- Operating position (OP): 19 ± 0.8mm



### SMJ2-1703BP

MICRO SWITCH MEDIUM ARM  
ROLLER MOMENTARY CONTACTS



- Material: Plastic, metal arm,  
plastic roller
- Position: On/Off, SPDT,  
1x N/O, 1x N/C, 3 x screw terminal
- Rating: 5A @ 24Vdc
- Operating temperature: -15°C to + 80°C
- Operating force (OF): 100g
- Releasing force (RF): 21g Min
- Pre-travel (PT): 7.1mm Max
- Over travel (OT): 4mm Min
- Travel differential (DT): 1.6mm Max
- Free position (FP): 36.5mm Max
- Operating position (OP): 30.2 ± 0.8mm

