

HEAT SHRINKABLE FULLY INSULATED CABLE JOINERS

- Material: Copper high-density
- Polyethylene (HDPE)
- Shrink temperature: +150 °C
- Operating temperature: - 40°C to + 105°C
- Max. voltage: 600V
- Double crimp



BLISTER/BOX



PRODUCT INFORMATION

Part No.	Colour	Wire Size	Qty	Packaging
LV2690	Red	2.5 - 3mm	10	Blister
LV2691	Red	2.5 - 3mm	50	Box
LV2692	Blue	4mm	10	Blister
LV2693	Blue	4mm	50	Box
LV2694	Yellow	5 - 6mm	10	Blister
LV2695	Yellow	5 - 6mm	50	Box

HEAT SHRINKABLE RING TERMINALS

- Material: Copper high-density
- Polyethylene (HDPE)
- Shrink temperature: +150 °C
- Operating temperature: - 40°C to + 105°C
- Max. voltage: 600V
- Double crimp



BOX



PRODUCT INFORMATION

Part No.	Colour	Wire Size	Ring Dia	Qty	Packaging
LV2820	Red	2.5 - 3mm	4.3mm	50	Box
LV2821	Red	2.5 - 3mm	5mm	50	Box
LV2822	Red	2.5 - 3mm	6.3mm	50	Box
LV2823	Blue	4mm	5mm	50	Box
LV2824	Blue	4mm	6.3mm	50	Box
LV2825	Blue	4mm	8.4mm	50	Box
LV2829	Yellow	5mm - 6mm	5.3mm	50	Box
LV2826	Yellow	5mm - 6mm	6.3mm	50	Box
LV2827	Yellow	5mm - 6mm	8.4mm	50	Box
LV2828	Yellow	5mm - 6mm	9.5mm	50	Box

NON INSULATED MALE BLADE TERMINALS

- Material: Brass or tin plated
- Operating temperature: +125°C



BAG



PRODUCT INFORMATION

Part No.	Material	Wire Size	Tab Size	Qty	Packaging
LV2720	Brass	2.5 - 3mm	2.8 x 0.8mm	100	Bag
LV2721	Brass	4mm	6.3 x 0.8mm	100	Bag
LV2722	Tin Plated	3 - 5mm	6.3 x 0.8mm	100	Bag