# ROADVISION

## **FEATURES**

- Stop/Tail Indicator or Stop/Tail Indicator & Reverse functions
- Integrated Retro Reflectors
- Multi-volt 10-30V DC input & low current draw
- 100,000HR rated LED lifespan with solid state technology
- Simple surface mount design
- · ADR approved for all functions
- · Light weight tough polycarbonate housing & lens















ADR Approved

ROADVISION's BR502 Series mini jumbo LED combination lamps deliver powerful performance in a compact, versatile design—ideal for all applications, including 4WDs, small, medium, and large trucks and trailers. Combining Stop, Tail, Indicator, Reflector, and optional Reverse functions into one tough, compact unit, the BR502 Series offers the perfect balance of size, durability, and visibility. Featuring maintenance-free LED technology, these lamps provide brighter output than traditional incandescent lights while drawing significantly less current. Built to endure harsh conditions, they feature unbreakable polycarbonate lenses, a rugged high-impact ABS housing, and are fully sealed against dust and water. With a 100,000-hour LED lifespan, the BR502 Series is a dependable fit-and-forget lighting solution for vehicles of all sizes.

# PART NUMBERS



#### BR502ARR

LED Rear Combination Lamp 10-30V Stop/Tail x 2/Indicator Triple Surface Mount 460x130x33mm

# PART NUMBERS



#### BR502ARW

LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Reverse Triple Surface Mount 460x130x33mm

| SPECIFICATIONS        | BR502ARR  | BR502ARW   |
|-----------------------|---|--|
| INPUT VOLTAGE         | 10-30 VDC   | 10-30 VDC  |
| NUMBER OF LEDS        | Indicator - 16 LEDs,<br>Stop/Tail - 32 LEDs,                      | Indicator - 16 LEDs,<br>Stop/Tail - 16 LEDs,<br>Reverse - 16 LEDs                  |
| CURRENT DRAW @ 13.8V  | Ind - 0.11A, Stop - 0.23A,<br>Tail - 0.04A @ 13.8V                | Ind - 0.11A, Stop - 0.11A,<br>Tail - 0.02A, Rev - 0.11A @ 13.8V                    |
| LENS CONSTRUCTION     | Polycarbonate   | Polycarbonate  |
| HOUSING CONSTRUCTION  | High Impact ABS   | High Impact ABS  |
| MOUNTING HOLE CENTRES | 280mm   | 280mm  |
| OVERALL DIMENSIONS    | 460 x 130 x 33mm  | 460 x 130 x 33mm   |
| CABLE LENGTH          | 300mm Tinned Copper   | 300mm Tinned Copper  |
| ADR APPROVAL          | ADR Approved for all functions                                    | ADR Approved for all functions   |
| WIRING                | Earth - White,<br>Stop - Red, Tail - Brown,<br>Indicator - Yellow | Earth - White, Stop - Red,<br>Tail - Brown, Indicator - Yellow,<br>Reverse - Black |

## LINE DIAGRAM

