



FEATURES

- Stop/Tail Indicator or Stop/Tail Indicator & Reverse functions
- Sequential Indicator
- Grey Glowtech tail light
- Integrated Retro Reflector
- Multi-volt 10-30V DC input & low current draw
- 100,000HR rated LED lifespan with solid state technology
- Simple surface mount design
- ADR approved for all functions
- Light weight tough polycarbonate housing & lens
- Mild tinted lens and gun metal grey chrome finish

LED COMBINATION LAMPS

MULTI-VOLT
10-30 VDC

PC
POLYCARB
LENS

PC
POLYCARB
HOUSING

IP67
WATERPROOF

ADR
APPROVED

SEQUENTIAL
INDICATOR

GLOW TAIL
LIGHT

5YR
5 YEAR
WARRANTY

Enhance your vehicle's lighting performance with the ROADVISION BR281 Series—designed to deliver style, safety, and reliability in one compact package. Combining Stop/Tail/Indicator or Stop/Tail/Indicator & Reverse functions with a striking sequential indicator, the BR281 Series offers a modern lighting solution that commands attention on the road. Featuring an integrated retro reflector for added visibility and ADR approval across all functions, these lamps are built with efficiency and durability in mind. The multi-volt 10–30V DC input and low current draw ensure compatibility with a wide range of vehicles, while the tough yet lightweight polycarbonate housing and lens provide long-lasting performance. Finished with a sleek mild tinted lens and gun metal grey chrome trim, the BR281 Series offers a clean, contemporary look that fits

PART NUMBERS

BR281ARR
LED Rear Combination Lamp 10-30V
Stop/Tail/Ind/Ref 200x100x37mm

PART NUMBERS

BR281ARW
LED Rear Combination Lamp 10-30V
Stop/Tail/Ind/Rev/Ref 200x100x37mm

SPECIFICATIONS	BR281ARR	BR281ARW
INPUT VOLTAGE	10-30 VDC	10-30 VDC
NUMBER OF LEDs	Indicator - 15 LEDs, Stop - 48 LEDs, Tail - 36 LEDs	Indicator - 15 LEDs, Stop - 32 LEDs, Tail - 36 LEDs, Reverse - 16 LEDs
CURRENT DRAW @ 13.8V	Ind - 0.29A, Stop - 0.33A, Tail - 0.14A @ 13.8V	Ind - 0.29A, Stop - 0.2A, Tail - 0.14A, Rev - 0.26A @ 13.8V
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Polycarbonate	Polycarbonate
MOUNTING HOLE CENTRES	120mm	120mm
OVERALL DIMENSIONS	280 x 100 x 37mm	280 x 100 x 37mm
CABLE LENGTH	300mm Tinned Copper	300mm Tinned Copper
CTA APPROVAL	CTA-061824	CTA-061819
WIRING	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black

LINE DIAGRAM

