

## FEMALE SOLENOID VALVE CONNECTORS/ DIN CONNECTORS



- PA-GF housing resists impact damage
- Red LED indicator in translucent housings conveniently signals machine status
- Operating temperature range of -25°C to +80°C to suit tough industrial settings

- IP rating: IP65
- Applications: Pressure sensors, pumping stations, refrigeration units & agricultural equipment

**SINGLE PACK**

### LV1800 12/24V TYPE C DIN CONNECTOR



#### SPECIFICATIONS:

- Housing dimensions: 15 x 15mm
- Housing material: Nylon-6 GF
- Housing colour: Black
- Height: 21mm
- Connection type: 2Pole + Earth
- Contact spacing: 8mm
- Central fixing screw: M2.5 x 22.5mm
- Gasket: Integrated NBR gasket
- Gland size: PG7
- Socket type: Type C
- Terminals: Screw type
- Current rating : 6A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 C

### LV1801 12/24V TYPE C DIN CONNECTOR RED LED INDICATOR & RESISTOR PROTECTED



#### SPECIFICATIONS:

- Housing dimensions: 15 x 15mm
- Housing material: Nylon-6 GF
- Housing colour: Transparent
- Height: 21mm
- Connection type: 2Pole + Earth
- Contact spacing: 8mm
- Central fixing screw: M2.5 x 22.5mm
- Gasket: Integrated NBR gasket
- Gland size: PG7
- Socket type: Type C
- Terminals: Screw type
- Current rating : 6A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 C

### LV1802 12/24V TYPE B DIN CONNECTOR



#### SPECIFICATIONS:

- Housing dimensions: 22 x 27.5mm
- Housing material: Nylon-6 GF
- Housing colour: Black
- Height: 22.9mm
- Connection type: 2Pole + Earth
- Contact spacing: 11mm
- Central fixing screw: M3 x 25mm
- Gasket: Integrated NBR gasket
- Gland size: PG9
- Socket type: Type B
- Terminals: Screw type
- Current rating : 10A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 B

### LV1803 12/24V TYPE B DIN CONNECTOR RED LED INDICATOR



#### SPECIFICATIONS:

- Housing dimensions: 22 x 27.5mm
- Housing material: Nylon-6 GF
- Housing colour: Transparent
- Height: 22.9mm
- Connection type: 2Pole + Earth
- Contact spacing: 11mm
- Central fixing screw: M3 x 25mm
- Gasket: Integrated NBR gasket
- Gland size: PG9
- Socket type: Type B
- Terminals: Screw type
- Current rating : 10A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 B