

BR125 SERIES

ROADVISION

FEATURES

- Stop/Tail Indicator or Stop/Tail Indicator & Reverse functions
- Integrated Retro Reflector
- Multi-volt 10-30V DC input & low current draw
- 100,000HR rated LED lifespan with solid state technology
- Simple surface mount design
- ADR approved for all functions
- Light weight tough polycarbonate housing & lens
- Mild tinted lens and gun metal grey chrome finish



MULTI-VOLT
10-30 VDC



POLYCARB
LENS



POLYCARB
HOUSING



WATERPROOF



ADR
APPROVED



5 YEAR
WARRANTY

Experience the perfect fusion of functionality and style with ROADVISION's BR125 Series. Designed to meet all your lighting needs, these all-in-one lamps seamlessly integrate Stop, Tail, Indicator, and Reverse functions into a contemporary, robust package. Engineered with advanced solid-state technology, the BR125 Series offers powerful illumination, enhanced safety, and a remarkable lifespan of up to 100,000 hours. Fully ADR-compliant, these lamps are crafted with a durable yet lightweight polycarbonate housing and lens, ensuring reliable performance in demanding conditions. The sleek tinted lens and gun metal grey chrome finish deliver a modern look, while the integrated retro reflector maximizes visibility for added safety. With its straightforward surface-mount design and maintenance-free operation, the BR125 Series is the go-to solution for dependable, stylish combination lighting.

PART NUMBERS



BR125ARR
LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Ref
125x32mm

PART NUMBERS



BR125ARW
LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Rev/Ref
125x32mm

SPECIFICATIONS	BR125ARR	BR125ARW
INPUT VOLTAGE	10-30 VDC	10-30 VDC
NUMBER OF LEDs	Indicator - 10 LEDs, Stop/Tail - 12 LEDs	Indicator - 5 LEDs, Stop/Tail - 12 LEDs, Reverse - 5 LEDs
CURRENT DRAW @ 13.8V	Ind - 0.25A, Stop - 0.19A, Tail - 0.03A @ 13.8V	Ind - 0.13A, Stop - 0.19A, Tail - 0.03A, Rev - 0.18A @ 13.8V
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Polycarbonate	Polycarbonate
MOUNTING HOLE CENTRES	45mm	45mm
OVERALL DIMENSIONS	125 x 32mm	125 x 32mm
CABLE LENGTH	300mm Tinned Copper	300mm Tinned Copper
CTA APPROVAL	CTA-061779	CTA-061782
WIRING	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black

LINE DIAGRAM

