BR602 SERIES

ROADVISION

FEATURES

- Stop/Tail Indicator or Stop/Tail Indicator & Reverse functions
- Integrated Retro Reflectors
- Multi-volt 10-30V DC input & low current draw
- 100,000HR rated LED lifespan with solid state technology
- Simple surface mount design
- ADR approved for all functions
- Light weight tough polycarbonate housing & lens
- Retro-fits in place of existing jumbo style lamps

LED COMBINATION LAMPS

MULTI-VOLT 10-30 VDC	POLYCARB LENS	HIGH IMPACT HOUSING	WATERPROOF	ADR APPROVED	5 YEAR WARRANTY

ROADVISION's BR602 Series LED jumbo combination lamps are the ultimate heavy-duty lighting solution for trucks and trailers, now with a refreshed design and enhanced styling. Featuring Stop, Tail, Indicator, Reflector, and optional Reverse functions all in one robust unit, the BR602 Series delivers maximum functionality without compromise. Engineered with maintenance-free LED technology, these lamps offer superior visibility and safety, while consuming only a fraction of the power of traditional incandescent lights. Built tough for demanding environments, the BR602 features unbreakable polycarbonate lenses and a rugged, high-impact ABS housing that is fully sealed against dust and water ingress. Rated to a 100,000-hour LED lifespan, the BR602 Series is a true fit-and-forget solution, ideal for those who demand reliability, performance, and durability in every kilometre.

PART NUMBERS

BR602ARR
LED Rear Combination Lamp 10-30V Stop/Tail x 2/Ind Jumbo Triple Surface Mount 604x132x46mm

PART NUMBERS

BR602ARW
LED Rear Combination Lamp 10-30V Stop/Tail/Ind/Rev Jumbo Triple Surface Mount 604x132x46mm

SPECIFICATIONS	BR602ARR	BR602ARW
INPUT VOLTAGE	10-30 VDC	10-30 VDC
NUMBER OF LEDS	Indicator - 16 LEDs, Stop/Tail - 32 LEDs,	Indicator - 16 LEDs, Stop/Tail - 16 LEDs, Reverse - 16 LEDs
CURRENT DRAW @ 13.8V	Ind - 0.11A, Stop - 0.23A, Tail - 0.04A @ 13.8V	Ind - 0.11A, Stop - 0.11A, Tail - 0.02A, Rev - 0.11A @ 13.8V
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	High Impact ABS	High Impact ABS
MOUNTING HOLE CENTRES	501mm & 325mm	501mm & 325mm
OVERALL DIMENSIONS	604 x 132 x 46mm	604 x 132 x 46mm
CABLE LENGTH	300mm Tinned Copper	300mm Tinned Copper
CTA APPROVAL	CTA-061847	CTA-061849
WIRING	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black

LINE DIAGRAM

325MM
501MM