

FEMALE SOLENOID VALVE CONNECTORS/ DIN CONNECTORS



- PA-GF housing resists impact damage
- Red LED indicator in translucent housings conveniently signals machine status
- Operating temperature range of -25°C to +80°C to suit tough industrial settings

- IP rating: IP65
- Applications: Pressure sensors, pumping stations, refrigeration units & agricultural equipment

SINGLE PACK

LV1804

12/24V TYPE A DIN CONNECTOR



SPECIFICATIONS:

- Housing dimensions: 30 x 30mm
- Housing material: Nylon-6 GF
- Housing colour: Black
- Height: 22.9mm
- Connection type: 2Pole + Earth
- Contact spacing: 18mm
- Central fixing screw: M3 x 25mm
- Gasket: Integrated NBR gasket
- Gland size: PG11
- Socket type: Type A
- Terminals: Screw type
- Current rating : 10A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 A



LV1805

12/24V TYPE A DIN CONNECTOR
RED LED INDICATOR



SPECIFICATIONS:

- Housing dimensions: 30 x 30mm
- Housing material: Nylon-6 GF
- Housing colour: Transparent
- Height: 22.9mm
- Connection type: 2Pole + Earth
- Contact spacing: 18mm
- Central fixing screw: M3 x 25mm
- Gasket: Integrated NBR gasket
- Gland size: PG11
- Socket type: Type A
- Terminals: Screw type
- Current rating : 10A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 A



LV1806

12/24V TYPE A DIN CONNECTOR
RED LED INDICATOR &
RESISTOR PROTECTED



SPECIFICATIONS:

- Housing dimensions: 30 x 30mm
- Housing material: Nylon-6 GF
- Housing colour: Transparent
- Height: 22.9mm
- Connection type: 2Pole + Earth
- Contact spacing: 18mm
- Central fixing screw: M3 x 25mm
- Gasket: Integrated NBR gasket
- Gland size: PG11
- Socket type: Type A
- Terminals: Screw type
- Current rating : 10A
- Contact resistance (initial): 20m Ohms max.
- Insulation resistance: 100M Ohms min.
- Rating: IP65
- Operating temperature: -25°C to +80°C
- Standards & approvals: DIN 43650 A

