

EMERGENCY STOP SWITCHES

SINGLE PACK

LV5020

NC/NO METAL CASE E-STOP SWITCH WITH LEGEND PLATE



- Material: Metal
- Contacts: 1 x N/O, 2 x N/C
- Latching/twist to reset
- Operating temperature: -25°C to +70°C
- Dimensions: 72 (W) x 74.5 (D) x 82mm Max (H)



LV5019

NO/NC METAL CASE E-STOP SWITCH WITH LEGEND PLATE



- Material: Metal
- Contacts: 1 x N/O, 2 x N/C (3A @ 240Vac)
- Latching/twist to reset
- Operating temperature: -25°C to +70°C
- Dimensions: 66.6 (W) x 66.5 (D) x 90mm Max (H)



ESP6/6

NC/NO PUSH/PULL E-STOP METAL PALM OPERATOR HEAD



- Voltage: 12V or 24V
- Aluminium housing
- Contacts: 1 x N/O, 1 x N/C (10A @ 12 or 24Vac)
- Push to stop, pull to release
- Function: On - Off - DPST
- 63.5mm Metal palm operator head
- IP rating: IP65
- Lockable in OFF position
- Dimensions: 95 x 95mm



10250T701M

NC/NO TWIST TO RELEASE E-STOP METAL MUSHROOM OPERATOR HEAD



- Aluminium housing
- Contacts: 1 x N/O, 1 x N/C (10A @ 12V)
- Push to stop, twist to release
- Function: On - Off - DPST
- 45mm Metal palm operator head
- IP rating: IP65
- Lockable in OFF position
- Dimensions: 95 x 95mm



LV5030

NC/NO PANEL MOUNT E-STOP SWITCH



- Material: Plastic
- Contacts: 1 x N/O, 1 x N/C (3A @ 240Vac)
- Latching/twist to reset
- Operating temperature: -25°C to +70°C
- Dimensions: 43 (W) x 40 (D) x 100mm Max (H)
- Mounting hole: Ø22mm



LV5022

NC/NC PANEL MOUNT E-STOP SWITCH



- Material: Plastic
- Contacts: 2 x N/C (3A @ 240Vac)
- Latching/twist to reset
- Operating temperature: -25°C to +70°C
- Dimensions: 43 (W) x 40 (D) x 100mm Max (H)
- Mounting hole: Ø22mm

