

Product Release

August 2020

GENIUS 10AU 6V & 12V 10A

Lithium Lead Acid MF **EFB AGM** Gel Li-lon

Auto | Marine | RV | Powersport | Lawn & Garden

NOCO 1 O BATTERY CHARGER HANDING TO HANDER



EVERYTHING CHARGER.

Do more with Genius. Multi-voltage, chemistries, and types.

Meet the GENIUS10 - Similar to our G7200, just better. It's 17% smaller and delivers over 115% more power. And it's simpler and easier to use than ever before. Plug-in, connect to the battery, select a charge mode, and start charging your battery. A fully-automatic, worry-free battery charger for year-round use. Designed for 6-volt and 12-volt lead-acid automotive, marine, and deep-cycle batteries. including flooded, gel, AGM, maintenance-free, and lithium-ion batteries.



CHARGE DOWN TO ZERO VOLTS.

Charge dead batteries as low as 1-volt. Or use the all-new Force Mode that allows you to take control and manually begin charging dead batteries down to zero volts.



BRING BATTERIES BACK TO LIFE.

Built-in desulfation mode for the most corroded batteries. Auto detection with smart diagnostic indicators starts a Repair Mode integrated within a 9-step charging



THFRMAI COMPENSATION.

An integrated thermal sensor detects the ambient temperature and alters the charge to eliminate over-charging in hot climates and under-charging in cold climates.

24/7

WORRY-FREE CHARGING.

Provides all-season, all-weather charging for a healthy battery. Leave plugged in 24/7 with no worries of overcharging. Automatically returns to its last selected mode.



Product Release

August 2020

WHAT'S IN THE BOX.



Charger + Interchangeable Connector

Battery Clamps + Integrated Eyelets



Mounting Bracket + Strap

(2) #8x1" Self-tapping Screws




User Guide

NOCO* Patented Technology Patented: visit no.co/patents

Maximum Versatility.

Genius clamps are built with needle-nose profiles for smaller terminal applications and detachable integrated eyelets for permanently mounting the accessory to the battery.



8.2in

2.3in

3.6in

Technical Specifications			
Line Voltage AC:	120-240 VAC, 50-60Hz	DC Cable Length:	77.6in/ 1.97m
Output Power:	150 Watts Max	AC Cable Length:	71.7in/ 1.82m
Charging Voltage:	Various	Back Current Drain:	<0.5mA
Charging Current:	10A (12V), 10A (6V)	Battery Capacity:	Up to 230Ah, Maintains All Battery Sizes
Chemistry:	Lead-Acid and Lithium	Housing Protection:	IP65
Operating Temperature:	-4° to 104° F (-20° to +40° C)	Dimensions (LxWxH):	7.1x3.6x2.3in / 180.3x91.4x58.4mm
Storage Temperature:	-22° to 140° F (-30° to +60° C)	Unit Weight:	3.33 lbs / 1.5kG
Low-Voltage Detection:	1V (12V), 1V (6V)	Cooling:	Natural Convection

Charging Times	(for reference, results may vary)	
Battery Size	Approx. Charge Time in Hours 6V 12V	
20Ah	1.5	1.5
40Ah	3	3
80Ah	6	6
100Ah	7	7
230Ah	17.3	17.3

WHAT'S IN THE BOX.

- GENIUS10 Battery Charger w/ Interchangeable Connector
- · Clamps w/ Integrated Eyelets
- Mounting Bracket w/ Strap
- (2) Self-Tapping Screws
- User Guide & Warranty Information

