


It's **DENSO** **RELAX**



• **ISS Relay**
• Fitted for increased starter system circuit reliability.

• **Housing**
• Designed to withstand the toughest applications and long life operation.

• **Supported Nose Cone**
• Rotatable supported nose cone for increased flexibility and heavy duty applications.



• • • • • **Pinion Gear**
Soft engagement for improved durability and high torque for maximum starting power.

• **Lightweight**
Class leader in size and weight for ease of installation.

**High torque.
Outstanding durability.
So you can be stress free.**

DENSO

ROTATING ELECTRICAL


It's DENSO, relax. It's no surprise that DENSO has the lowest return rate in the industry. Our starter motors undergo stringent quality tests, are then thrown off cliffs and into pits with live snakes to ensure they come out tough. Need to improve your efficiency and profitability? Stop whimpering out. Switch to a DENSO P.8 and 'RELAX' knowing your starter will pull you through.

P8.0 Starter Motor

SPECIFICATIONS

Brands	Caterpillar, Cummins, Detroit, John Deere
Rated Voltage & Output	24V 8.0 kW (10.7 HP)
Mount	SAE #3
	180° housing opening for flywheel
Rotation	Clockwise
Approximate Weight	18 kgs
Warranty	2years / 150,000Kms* (On-Road applications) *1 year / 2000 hours of operation for mining, agricultural and industrial applications

PERFORMANCE



PART NUMBERS

428000-1450

Pinion: 12 Tooth (DP6/8) (Crosses with competitor's 11 tooth big gear design)


428000-1440

Pinion: 13 Tooth (DP8/10) (Crosses with competitor's 12 tooth small gear design)



SIZE COMPARISON

DENSO R5
10.5KG



DENSO P8.0
18.4KG



Delco-Remy 39MT
15.5KG



Delco-Remy 42MT
25.5KG

