

DC-DC CHARGER KIT WITH INTELLI-IQ DISPLAY

**Charger Features:**

- Intelli-charge DC-DC battery charger with Linbus MPPT solar
- Control & monitor remotely via smartphone or Intelli-IQ interface
- Bluetooth connectivity
- 3 & 5 Stage charging (parallel charging)
- Operating temperature: -10°C to +90°C
- Types: WET, CA, AGM, GEL, LiFePO4
- ECE R10
- IP68 & IP69K

IQD2 Features:

- Real-time monitoring of device operating status
- Plug & play system
- Bluetooth
- Touch screen
- Auto brightness



PRODUCT INFORMATION

Part No.	Input Voltage	Output Current	Max Solar Input	Dimensions
IDC25XIQ	9-32V DC	25A	32V DC 400W	137 x 122 x 50mm
IDC50XIQ	9-32V DC	50A	32V DC 800W	138 x 121 x 71mm

DC-DC CHARGERS



- Intelli-charge DC-DC battery charger with Linbus MPPT solar
- Bluetooth connectivity
- 3 & 5 Stage charging (parallel charging)
- Operating temperature: -10°C to +90°C
- Types: WET, CA, AGM, GEL, LiFePO4
- ECE R10
- IP68 & IP69K



PRODUCT INFORMATION

Part No.	Input Voltage	Output Current	Max Solar Input	Dimensions
IDC25X	9-32V DC	25A	32V DC 400W	137 x 122 x 50mm
IDC50X	9-32V DC	50A	32V DC 800W	138 x 121 x 71mm