

HIGH CAPACITY FLASHER UNITS

Universal Flasher Unit Metal Bracket

8003

For mounting round HELLA Flasher Units – 32mm diameter.



SOLID STATE ELECTRONIC FLASHER UNITS


Solid State Electronic Flasher Unit - 3 Pin, 12V DC

3016

To operate 2 or 3 lamps on either side of vehicle. Incorporates hazard warning flasher system when used in conjunction with HELLA switch Part No. 5227.

Voltage	12V DC
Max Load	2(4) x 21W + 0-5W
Replaces	Ford 78DA 13350AA, ASF-3 Toyota T340 81 026, 81980-220616 Nissan 25520-V9600, 25730-J7000 GMH 92017464

Pin & Wiring



Note For common pin designations, refer to page 395




Solid State Electronic Flasher Unit - 3 Pin, 12V DC

3016LED1

Specifically designed for use with DuraLed® Rear Direction Indicator Lamps on motor vehicles, such as prime movers, trucks and motor homes, maintaining the mandatory ADR specified globe failure warning signal function.

Voltage	12V DC
Max Load	Front Direction Indicator Lamp 1(2) x 21W DuraLed Rear Direction Indicator Lamp 1(2) x 9W

Pin & Wiring



Note For common pin designations, refer to page 395

