

24V MINI & HIGH POWER RELAYS




SINGLE PACK

LV4516

24V/30A 4 PIN FUSED MINI RELAY
SPST N/O CIRCUIT



- Voltage: 24V
- Amperage: 30A
- Silver contacts
- Resistor protected
- 30A ATS Blade Fuse
- Removable mounting bracket
- Operating temperature: -40°C to +80°C
- No. of pins: 4



E50-0012

24V/40A 4 PIN MINI RELAY
SPST N/O CIRCUIT


- Voltage: 24V
- Amperage: 40A
- Silver contacts
- Resistor protected
- Removable mounting bracket
- Operating temperature: -40°C to +125°C
- No. of pins: 4



LV4547

24V/11A 4 PIN MINI RELAY
SPST N/O CIRCUIT



- Voltage: 24V
- Amperage: 11A
- No. of pins: 4
- Applications: Toyota
- Reference: 90987-02005



E50-0014

24V/70A 4 PIN HIGH AMP
MINI RELAY
SPST N/O CIRCUIT


- Voltage: 24V
- Amperage: 70A
- Silver contacts
- Resistor protected
- Removable mounting bracket
- Operating temperature: -40°C to +125°C
- No. of pins: 4



R4-2480RBX

24V/80A 4 PIN MINI RELAY
SPST N/O CIRCUIT

- Voltage: 24V
- Amperage: 80A
- Silver contacts
- Resistor protected
- Removable bracket
- Operating temperature: -40°C to +125°C
- Sealed type
- No. of pins: 4



LV4507

24V/60A HEAVY DUTY
POWER RELAY
SPST N/O CIRCUIT

- Voltage: 24V
- Amperage: 60A Cont./80A Peak
- Housing material: Nylon PA6
- M6 tin plated copper studs x 2
- 6.3mm Brass push-on terminals x 2
- Includes mounting bracket
- Operating temperature: -40°C to +80°C
- No. of pins: 4

