




6MM SINGLE CORE MARINE CABLE

ROLL

- Conductor: Tinned copper wire (TCW) to AS/NZS 1125
- Insulation: RoHS Compliant V90HT (105) P.V.C. to AS/NZS 3808
- Voltage: 250/440V
- Applications: Pleasure craft, general purpose marine wiring
- Conductor: 57 Strands x Ø0.32mm
- Nominal area: 4.59mm²
- Current rating: 48A@30°C
- Insulation thickness: 0.6mm
- Resistance@20°C: 4.15Ohm/km
- Nominal O.D: 4mm
- Mass: 5.3Kg/100m




PRODUCT INFORMATION

Part No.	Colour	Length(m)
CB006M1-030BK	Black	30
CB006M1-050BK	Black	50
CB006M1-030RD	Red	30
CB006M1-050RD	Red	50

TWO CORE TWIN SHEATH MARINE CABLE

- Conductor: Tinned copper wire (TCW) to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: 50Vac or 120Vdc
- Applications: Trailer wiring/general purpose automotive wiring
- Core colour: Black & Red
- Insulation thickness: 0.4mm; 0.6mm for 6mm
- Sheath colour: White
- Sheath thickness: 0.6; 0.8 for 6mm



PRODUCT INFORMATION

Part No.	Size (mm)	Area (mm ²)	Amp@30°C	Length (m)	Strands/Dia.	Resistance(Ohm/km)	O.D (mm)	Mass (kg/100m)
CB002M2-100BKRD	2	0.5	7	100	16/0.2	39	3.2 x 5.2	2.6
CB003M2-050BKRD	3	1.13	16	50	14/0.32	16.7	3.3 x 5.5	4.1
CB004M2-030BKRD	4	1.8	22	30	23/0.32	10.2	3.8 x 6.3	6.1
CB004M2-050BKRD	4	1.8	22	50	23/0.32	10.2	3.8 x 6.3	6.1
CB004M2-100BKRD	4	1.8	22	100	23/0.32	10.2	3.8 x 6.3	6.1
CB006M2-030BKRD	6	4.5	38	30	57/0.32	4.15	5.7 x 9.6	14
CB006M2-050BKRD	6	4.5	38	50	57/0.32	4.15	5.7 x 9.6	14