

BR218 SERIES

ROADVISION™

FEATURES

- Stop/Tail, Indicator, Reverse functions
- Reflector incorporated into lens
- Smoked lens
- Multi-volt 10-30V DC input & low current draw
- 100,000HR LED lifespan with solid state technology
- Simple surface mount design
- ADR approved for all functions
- Light weight tough ABS housing & polycarbonate lens



ROADVISION's BR218 Series LED combination lamps are a complete all-in-one fit and forget solution. Featuring smoked lenses, built in reflector, and a simple surface mount, the BR218 Series add a touch of class to your 4x4 and are equally at home in any industrial application. Delivering the durability of maintenance free technology, they provide greater visibility for increased safety and minimum current draw. Constructed with durable polycarbonate lenses and ABS housings, the BR218 Series is designed and built to survive the toughest environments.

PART NUMBERS



BR218ARW

LED Combination Light 10-30V Stop/Tail, Indicator, Reverse

PART NUMBERS



BR218ARR

LED Combination Light 10-30V Stop/Tail, Indicator

SPECIFICATIONS	BR218ARW	BR218ARR
INPUT VOLTAGE	10-30 VDC	10-30 VDC
NUMBER OF LEDS	24 LEDS: Indicator - 6 LEDS, Stop/Tail - 12 LEDS, Reverse - 6 LEDS	24 LEDS: Indicator - 6 LEDS, Stop/Tail - 12 LEDS, Reverse - 6 LEDS
CURRENT DRAW @ 13.8V	Ind - 0.23A, S/T - 0.1/0.02A, Rev - 0.16A @ 13.8V	Ind - 0.23A, S/T - 0.1/0.02A, Rev - 0.16A @ 13.
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	High Impact ABS	High Impact ABS
MOUNTING HOLE CENTRES	193mm	193mm
DIMENSIONS AXBXC	218 x 92 x 25mm	218 x 92 x 25mm
CABLE LENGTH	500mm Tinned Copper	500mm Tinned Copper
ADR APPROVAL	All functions ADR approved	All functions ADR approved
CTA APPROVAL	CTA-060960	CTA-060961
WIRING	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black	Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow, Reverse - Black

LINE DIAGRAM

