

BATTERY MASTER SWITCHES

SINGLE PACK


Cole Hersee
A Littelfuse® Brand

75903BX

BATTERY MASTER SWITCH WITH FIELD CIRCUIT



- Continuous/peak 5 sec rating: 125A/ 1000A, DPST
- Material: Plated steel cases, chrome plated lever, copper contacts
- Battery: 2 x 3/8" - 24 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- Dimensions: 67.3 (D) x 110mm Max (H)




75904BX

BATTERY MASTER SWITCH WITH FIELD CIRCUIT



- Continuous/peak 5 sec rating: 125A/ 1000A, DPST
- Material: Plated steel cases, silver plated lever, copper contacts
- Battery: 2 x 3/8" - 24 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- Dimensions: 67.3 (D) x 110mm Max (H)



75904-03BX

KEY OPERATED BATTERY MASTER SWITCH WITH FIELD CIRCUIT



- Continuous/peak 5 sec rating: 125A/ 1000A, DPST
- Material: Plated steel case, silver contacts
- Battery: 2 x 3/8" - 24 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- With locator pin
- Dimensions: 67.3 (D) x 86mm Max (H)



75907BX

BATTERY MASTER SWITCH WITH FIELD CIRCUIT



- Continuous/peak 5 sec rating: 300A/ 2000A, DPST
- Material: Plated steel case, chrome plated lever, silver contacts
- Battery: 2 x 1/2" - 20 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- With locator pin
- Dimensions: 67.3 (D) x 110mm Max (H)



75910BX

BATTERY MASTER SWITCH WITH FIELD CIRCUIT



- Continuous/peak 5 sec rating: 125A/ 1000A, DPST
- Material: Plated steel case, chrome plated lever, silver contacts
- Battery: 2 x 3/8" - 24 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- With locator pin
- Dimensions: 67.3 (D) x 110mm Max (H)



75912BX

BATTERY MASTER SWITCH



- Continuous/peak 5 sec rating: 125A/ 750A, DPST
- Material: Plated steel cases, chrome plated lever, silver contacts
- Battery: 4 x 3/8" -24 studs
- Field terminal: 2 x 10 - 32 (20A cont)
- Stem: Ø3/4" -24 thread, L-13mm, O'Ring sealed
- With locator pin
- Dimensions: 67.3 (D) x 110mm Max (H)

