




SINGLE CORE MARINE BATTERY CABLE

ROLL

- Conductor: Tinned copper wire (TCW) to AS/NZS 1125
- Insulation: RoHS Compliant V90HT (105) P.V.C. to AS/NZS 3808
- Voltage: 50Vac or 120Vdc
- Applications: Pleasure craft, general purpose marine wiring
- Insulation thickness: 0.6mm
- Resistance@20°C: 4.15Ohm/km
- Nominal O.D: 4mm
- Mass: 5.3Kg/100m



PRODUCT INFORMATION

Part No.	Size (B&S)	Area (mm ²)	Amp@30°C	Colour	Length (m)	Strands/Dia.	Ins. Thickness (mm)	Resistance (Ohm/km)	O.D (mm)	Mass (kg/100m)
CB108M1-030BK	8	8	74	Black	30	96/0.32	0.9	2.5	5.75	9.2
CB108M1-030RD	8	8	74	Red	30	96/0.32	0.9	2.5	5.75	9.2
CB106M1-030BK	6	13.5	103	Black	30	168/0.32	1.1	1.42	7.2	15.6
CB103M1-030BK	3	25.7	168	Black	30	329/0.32	1.6	0.79	10.2	29.2
CB103M1-030RD	3	25.7	168	Red	30	329/0.32	1.6	0.79	10.2	29.2
CB103M1-100BK	3	25.7	168	Black	100	329/0.32	1.6	0.79	10.2	29.2
CB103M1-100RD	3	25.7	168	Red	100	329/0.32	1.6	0.79	10.2	29.2
CB102M1-030BK	2	32	188	Black	30	399/0.32	1.7	0.62	10.3	36.5
CB102M1-030RD	2	32	188	Red	30	399/0.32	1.7	0.62	10.3	36.5

TWO CORE TWIN SHEATH MARINE BATTERY CABLE

- Conductor: Tinned copper wire (TCW) to AS/NZS 1125
- Insulation: V90 PVC to AS/NZS3808
- Voltage: 50Vac or 120Vdc
- Applications: Marine, Battery feeds, chargers, winches, power & solar generators
- Core colour: Black & Red
- Insulation thickness: 0.4mm; 0.6mm for 6mm
- Sheath colour: Black
- Sheath thickness: 0.9mm



PRODUCT INFORMATION

Part No.	Size (B&S)	Area (mm ²)	Amp@30°C	Length (m)	Strands/Dia.	Resistance@20°C (Ohm/km)	O.D (mm)	Mass (kg/100m)
CB108M2-030BKRD	8	7.7	59	30	96/0.32	2.43	7.1 x 12.5	22
CB106M2-030BKRD	6	13.5	82	30	168/0.32	1.42	8.8 x 16.0	36
CB102M2-030BKRD	2	32	150	30	399/0.32	0.61	13.0 x 24.0	83