

## BATTERY MASTER SWITCHES

SINGLE PACK



### LV5049

RED KEY BATTERY MASTER SWITCH KEY REMOVABLE IN OFF POSITION

- Continuous/peak 5 sec rating: 75A/ 300A, SPST
- Material: Thermoplastic body, copper contacts
- Battery: 2 x M10 studs
- Operating temperature: -40°C to +85°C
- Mounting cnt to cnt: 39mm
- Dimensions: 57.5 (D) x 103mm Max (H)
- IP rating: IP61
- \* Replacement key: **LV5049-KEY**



### LV5016

BATTERY ISOLATOR/E-STOP SWITCH WITH LED INDICATOR

- Amperage: 300A@12V; 150A@24V cont.
- Cranking: 1000A@12V; 800A@24V (5 sec.)
- SPST, N/C contact
- Push to turn off & twist to release
- Mushroom head: Ø40mm
- Copper studs: M10 x 1.5
- Cutout hole Ø25mm
- Mounting hole: Ø5.6mm
- Ignition Protected
- Red LED
- IP rating: IP66



### LV4953

BATTERY MASTER SWITCH WITH RED HANDLE

- Continuous/peak 5 sec rating: 250A/ 1000A, SPST
- Material: Thermoplastic body, metal flange, copper contacts
- Battery: 2 x M10 studs
- Stem: Ø31mm
- Operating temperature: -40°C to +85°C
- Dimensions: 64 (D) x 136mm Max (H)
- IP rating: IP67



### LV4950

LOCKABLE BATTERY MASTER SWITCH NON-REMOVABLE HANDLE

- Continuous/peak 5 sec rating: 250A/ 2500A, SPST
- Material: Thermoplastic body, metal flange, silver contacts
- Battery: 2 x M10 studs
- Stem: Ø24mm
- Mounting cnt to cnt: 100mm
- Operating temperature: -40°C to +85°C
- Dimensions: 64 (D) x 149mm Max (H)
- IP rating: IP65
- Supplied with with 3 x colour boots, on/off decal



### LV4951

BATTERY MASTER SWITCH WITH REMOVABLE HANDLE IN OFF POSITION

- Continuous/peak 5 sec rating: 250A/ 2500A, SPST
- Material: Thermoplastic body, metal flange, copper contacts
- Battery: 2 x M10 studs
- Stem: Ø24mm
- Mounting cnt to cnt: 100mm
- Operating temperature: -40°C to +85°C
- Dimensions: 64 (D) x 150mm Max (H)
- IP rating: IP65
- \* Replacement key: **LV4951-KEY**



### LV4952

BATTERY MASTER SWITCH WITH REMOVABLE HANDLE IN OFF POSITION

- Continuous/peak 5 sec rating: 250A/ 2500A, DPST
- Material: Thermoplastic body, metal flange, copper contacts
- Battery: 4 x M10 studs
- Stem: Ø24mm
- Mounting cnt to cnt: 120mm
- Operating temperature: -40°C to +85°C
- Dimensions: 68 (D) x 150mm Max (H)
- IP rating: IP66

