

BATTERY MASTER SWITCHES

SINGLE PACK

0341003004

BATTERY MASTER SWITCH
WITH REMOVABLE HANDLE IN
OFF POSITION



- Continuous/peak 5 sec rating: 250A/ 2500A, DPST
- Material: Thermoplastic body, metal flange, silver contacts
- Battery: 4 x M10 studs
- Stem: Ø24mm
- Mounting cnt to cnt: 120mm
- Dimensions: 68 (D) x 150mm Max (H)
- IP rating: IP66



0341003006

BATTERY MASTER SWITCH
WITH REMOVABLE HANDLE IN
OFF POSITION



- Continuous/peak 5 sec rating: 500A/ 3500A, DPST
- Material: Thermoplastic body, metal flange, silver contacts
- Battery: 4 x M10 studs
- Stem: Ø24mm
- Mounting cnt to cnt: 120mm
- Dimensions: 68 (D) x 150mm Max (H)
- IP rating: IP6K6K



LV5012

BATTERY MASTER SWITCH



- Voltage: 0 - 32V
- Amperage: 500A cont. ; 2500A/10 secs. ; 2000A/75 secs.
- Aux. contact: 2A cont.
- Type: DPST battery
- In-built lock-out
- Case material: PA GF black
- Switch lever: PA GF red
- Operating temperature: -40°C to +85°C
- Comes with connector **DT06-4S-E008**
- Silver contacts
- Mounting ctn to ctn: 100mm
- Mounting hole: Ø8.5mm
- Stud size: M12 x 4
- IP rating: IP67
- Kissling



BMS524R

BATTERY MASTER SWITCH



- Voltage: 0 - 32V
- Amperage: 500A cont. ; 2500A/10 secs. ; 2000A/75 secs.
- Type: DPST battery
- In-built lock-out
- Operating temperature: -40°C to +85°C
- Silver contacts
- Mounting ctn to ctn: 100mm
- Mounting hole cut out: Ø85mm
- Mounting hole: Ø8.5mm
- Stud size: M12 x 4
- IP rating: IP67
- Kissling



BMS524Y

BATTERY MASTER SWITCH



- Voltage: 0 - 32V
- Amperage: 500A cont. ; 2500A/10 secs. ; 2000A/75 secs.
- Type: DPST battery
- In-built lock-out
- Operating temperature: -40°C to +85°C
- Silver contacts
- Mounting ctn to ctn: 100mm
- Mounting hole cut out: Ø85mm
- Mounting hole: Ø8.5mm
- Stud size: M12 x 4
- IP rating: IP67
- Kissling



BMS514R

BATTERY MASTER SWITCH



- Voltage: 0 - 32V
- Amperage: 500A cont. ; 2500A/10 secs. ; 2000A/75 secs.
- Type: SPST batter
- In-built lock-out
- Operating temperature: -40°C to +85°C
- Silver contacts
- Mounting ctn to ctn: 100mm
- Mounting hole cut out: Ø70mm
- Mounting hole: Ø8.5mm
- Stud size: M12 x 4
- IP rating: IP67
- Kissling

