


LV5450

4 WAY STANDARD BLADE FUSE HOLDER

- Voltage: 6 - 32V
- Fuse rating: 3 - 40A
- Housing material: Nylon PA66
- Terminals: Brass
- Stackable style
- Axial/bottom cable entry
- Busbar included
- Mounting hole: 5.5mm




SINGLE PACK


LV5440

4 WAY MINI & STANDARD FUSE BLOCK SUITS MINI, ATS & MICRO 2 FUSES

- Voltage: 6 - 32V
- Fuse rating: 3 - 40A
- Housing material: Thermoplastic
- Weatherproof clear cover with rubber seal
- Terminal material: Tin plated
- Terminals: 6.3mm push-on
- Mounting hole: 5mm
- * Wide surface area contacts



SINGLE PACK




LV5441

6 WAY MINI & STANDARD FUSE BLOCK SUITS MINI, ATS & MICRO 2 FUSES

- Voltage: 6 - 32V
- Fuse rating: 3 - 40A
- Housing material: Thermoplastic
- Weatherproof clear cover with rubber seal
- Terminal material: Tin plated
- Terminals: 6.3mm push-on
- Mounting hole: 5mm
- * Wide surface area contacts



SINGLE PACK



LV5442

8 WAY MINI & STANDARD FUSE BLOCK SUITS MINI, ATS & MICRO 2 FUSES

- Voltage: 6 - 32V
- Fuse rating: 3 - 40A
- Housing material: Thermoplastic
- Weatherproof clear cover with rubber seal
- Terminal material: Tin plated
- Terminals: 6.3mm push-on
- Mounting hole: 5mm
- * Wide surface area contacts



SINGLE PACK

