


Micro Switches

E52-3506

Micro Switch


- Micro Switch - Push Roller Nut Right
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 250 - 450g
- RF Min: 114g
- PT Max: 0.5mm
- OT Min: 3.58mm
- DT Max: 0.05mm
- OP: $49.7 \pm 1.2\text{mm}$



E52-3507

Micro Switch


- Micro Switch - Medium Push Button
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 540g
- RF Min: 114g
- PT Max: 1.9mm
- OT Min: 1.6mm
- DT Max: 0.06mm
- OP: $28.2 \pm 0.5\text{mm}$



E52-3508

Micro Switch


- Micro Switch - Medium Push Button
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 540g
- RF Min: 114g
- PT Max: 2.3mm
- OT Min: 1.6mm
- DT Max: 0.06mm
- OP: $28.2 \pm 0.5\text{mm}$



E52-3509

Micro Switch


- Micro Switch - Medium Arm
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 70g
- RF Min: 14g
- PT Max: 10.0mm
- OT Min: 5.6mm
- DT Max: 1.27mm
- FP Max: 28.2mm
- OP: $19.0 \pm 0.8\text{mm}$



E52-3510

Micro Switch

- Micro Switch - Short Arm
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 120g
- RF Min: 20g
- PT Max: 7.9mm
- OT Min: 3.0mm
- DT Max: 1.0mm
- FP Max: 26.2mm
- OP: $19.0 \pm 0.8\text{mm}$



E52-3511

Micro Switch

- Micro Switch - Medium Arm Roller
- Temperature Range $-15^{\circ}\text{C} > 80^{\circ}\text{C}$
- Momentary Contacts
- Completely Sealed Construction
- OF Max: 100g
- RF Min: 21g
- PT Max: 7.1mm
- OT Min: 4.0mm
- DT Max: 1.6mm
- FP Max: 36.5mm
- OP: $30.2 \pm 0.8\text{mm}$

