

LV1009HD Voltage Control Relay 12/24V

- Dual Voltage 12/24V
- 140 Amp
- Microprocessor Controlled
- Automatically Detects Voltage
- Bi-Directional Charging
- Gastight Contacts
- Prevents excessive discharging of the starter battery
- Priority for charging only the starter battery first
- Easy to Install
- No Voltage Drop
- 2 Years Warranty
- Made in Europe



Specifications:

Operating Voltages	12V	24V
Relay Turn On Voltage	13.2V	26.4V
Relay Turn Off Voltage:	12.8V	25.6V
Operating Range:	Min -30°C	Max +75°C
Warning Light:	-	
Maximum Voltage Drop:	< 200mV at full load	
Easy Connection:	M8 screw terminals	
Dimensions (LxWxH):	80 x 46 x 46mm	
Weight:	110g	

Note: Cable Kit Part No **LV1009CABLE**

LV1010HD Voltage Control Relay 12/24V

- Dual Voltage 12/24V
- 160 Amp
- Microprocessor Controlled
- Automatically Detects Voltage
- Bi-Directional Charging
- Gastight Contacts
- Prevents excessive discharging of the starter battery
- Priority for charging only the starter battery first
- Easy to Install
- No Voltage Drop
- 2 Years Warranty
- Made in Europe



Specifications:

Operating Voltages	12V	24V
Relay Turn On Voltage	13.2V	26.4V
Relay Turn Off Voltage:	12.8V	25.6V
Operating Range:	Min -30°C	Max +75°C
Warning Light:	✓	
Maximum Voltage Drop:	< 200mV at full load	
Easy Connection:	M8 screw terminals	
Dimensions (LxWxH):	108 x 72 x 58mm	
Weight:	470g	

Note: Cable Kit Part No **LV1010CABLE**