

SOLENOIDS

SINGLE PACK

684-1251-232-02

12V 300A INTERMITTENT DUTY
SOLENOID N/O CONTACTS



TROMBETTA

- Contact rating: 200A cont.
- Peak inductive inrush: 1000A
- Contacts: Silver alloy
- Contact life: 50,000 cycles
- Cycle: Intermittent
- Insulation: Ungrounded
- Coil terminals: 10-32 studs
- Contact terminals: 5/16-24 studs
- Operating temperature: -40°C to +65°C
- Sealing: IP66 & IP67



684-2451-232-02

24V 150A INTERMITTENT DUTY
SOLENOID N/O CONTACTS



TROMBETTA

- Contact rating: 200A cont.
- Peak inductive inrush: 1000A
- Contacts: Silver alloy
- Contact life: 50,000 cycles
- Cycle: Intermittent
- Insulation: Ungrounded
- Coil terminals: 10-32 studs
- Contact terminals: 5/16-24 studs
- Operating temperature: -40°C to +65°C
- Sealing: IP66 & IP67



214-1231-A61-06

12V 75A FORWARD/REVERSE
SOLENOID N/O CONTACTS



TROMBETTA

- Contact rating: 75A for 5mins.
- Peak inrush: 500A
- Contacts: Silver
- Contact life: 5000 cycles
- Cycle: Intermittent
- Insulation: Ungrounded
- Coil terminals: 1/4" (6.35mm) QC terminals
- Contact terminals: 5/16-24 studs
- Operating temperature: -40°C to +60°C
- Sealing: Unsealed




214-2431-A61-06

24V 75A FORWARD/REVERSE
SOLENOID N/O CONTACTS



TROMBETTA

- Contact rating: 75A for 5mins.
- Peak inrush: 500A
- Contacts: Silver
- Contact life: 5000 cycles
- Cycle: Intermittent
- Insulation: Ungrounded
- Coil terminals: 1/4" (6.35mm) QC terminals
- Contact terminals: 5/16-24 studs
- Operating temperature: -40°C to +60°C
- Sealing: Unsealed




LV5702

12V AUX FORD STARTER SOLENOID
FIREWALL MOUNT TYPE INSULATED BASE



LV
automotive™

- Material: Plastic housing
- Battery Studs: 2 x copper stud (8-32)
- Coil studs: 2 x stud terminals (10-32)
- Cnt to cnt: 55mm
- Dimensions: Ø54.5 x (L) 78.6mm
- Application: Ford, Delco, Johnson Electric
- Reference: U930, U939, 5130440, SW3, B6AZ11450A, D8DZ11450A, SW1080A, SW1162, SW246, SW1507,A,B, SW246, SW904



LV5709

12V LUCAS STARTER SOLENOID
FIREWALL MOUNT TYPE



LV
automotive™

- Material: Steel-plated housing, rubber push button
- Battery Studs: 2 x copper stud (M8)
- Coil studs: 2 x blade terminals
- Dimensions: Ø54.5 x (L) 78.6mm
- Application: Lucas, Perkins
- Reference: 76415, 76417, 76425, 76426, 76445, 76450, 76460, 76464, 76465, 76470, 76471, 76485, 76486, 76703

