NCCO 2 CHARGER & CHARGER & MAINTAINER



GENIUS2AU

CHARGING CURRENT

6V & 12V

30W OUTPUT POWER

40Ah BATTERY CAPACITY

GENIUS CHARGERS

ACCESSORIES

OVERVIEW



What's In The Box

- Genius 2 Battery Charger w/ Interchangeable Connector

 • Clamps w/ Integrated Eyelets
- Mounting Bracket w/ Strap
- (2) Self-Tapping Screws
- User Guide & Warranty Information

Retail Packaging

Dimensions: 3.43" x 4.25" x 6.97"

Weight: 1.23lbs

UPC: 0-46221-19003-8

Inner Carton:

Dimensions: 3.70" x 4.49" 7.20" Weight: 1.28lbs

Master Carton:

Dimensions: 15.12" x 11.81" x 5.20" Weight: 8.44lbs Quantity: 6 UCC: 10046221190035

Units Per Pallet:

378 Units



PROPRIETARY AND CONFIDENTIAL. COPYRIGHT © 2019 THE NOCO COMPANY


THIS DOCUMENT CONTAINS PROPRIETARY, CONFIDENTIAL, COPYRIGHTED, AND TRADE SECRET INFORMATION OF THE NOCO COMPANIES ("NOCO"). ALL MATERIAL, INFORMATION, AND CONTENT ARE THE PROPERTY OF NOCO, AND NOCO RETAINS ALL RIGHT, TITLE, AND INTEREST THEREIN. THIS DOCUMENT MAY NOT BE COPIED, DISSEMINATED, DISCLOSED, PUBLISHED, DIVULGED, OR REPRODUCED, IN WHOLE OR IN PART, WITHOUT THE PRIOR WRITTEN CONSENT OF NOCO. TITLE IN AND TO THIS DOCUMENT (NO MATTER IF IN PRINTED, ELECTRONIC, OR ANY OTHER FORM) AND ALL INFORMATION CONTAINED HEREIN REMAINS AT ALL TIMES IN NOCO. NO INTELLECTUAL PROPERTY RIGHTS ARE TRANSFERRED TO YOU BY ACCESS TO THIS DOCUMENT OR OTHERWISE. V10.07.19A 21

/ERVIEW

TECH SPECS

OMPARE

NCCO 7 TECH Genius 2 SPECS



GENIUS2AU

Operating Requirements

Line Voltage AC: 120V to 240V AC, 50-60Hz

Operating Temperature: -4° to 104° F (-20° to $+40^{\circ}$ C) Storage Temperature: -22° to 140° F (-30° to $+60^{\circ}$ C)

Relative Humidity: 0 to 95% Non-Condensing

Charging

Current: 2 Amp DC **Voltages:** 6V, 12V

Chemistry: Lead-Acid and Lithium

Types: Wet, Gel, MF, CA, EFB, AGM, Lithium **Battery Capacity Range:** 1.2 Ah - 40 Ah

Maintenance: All Battery Sizes

Power

Output Power: 30 Watts (Max) Efficiency: 87% (120VAC / 230VAC)

Protection

IP Rating: IP65

Safety

Short Circuit: Yes
Open-Circuit: Yes
Overheating: Yes
Overcharge: Yes
Spark-Proof Yes
Reverse Polarity: Yes

Size and Weight

Height: 3.7 Inches (94mm)
Width: 2.4 Inches (61mm)
Depth: 1.7 Inches (43mm)
Weight: 1.1 Pounds (0.5kg)

Cord Management

DC Cable Length: 77.6 Inches (197cm)

DC Cable Size: 18 AWG

DC Fuse Size: 4 AMP Micro Blade Fuse **AC Cable Length:** 71.7 Inches (182cm)

AC Cable Size: 18 AWG

Oil, gas, grease, water, chemical, UV, abrasion resistant

Limited Warranty

3-Year Limited Warranty

Charging Times


Battery Size	Approx. Charge Time in Hours	
	6V	12V
8Ah	3	3
12Ah	4.5	4.5
18Ah	6.75	6.75
24Ah	9	9
40Ah	15	15



PROPRIETARY AND CONFIDENTIAL. COPYRIGHT © 2019 THE NOCO COMPANY

NCCO 2 CHARGER COMPARISON

GENIUS2AU



MORE POWER SMALLER SIZE

45% 37% LITHIUM SMART

CHARGE MODE INDICATORS



PROPRIETARY AND CONFIDENTIAL. COPYRIGHT © 2019 THE NOCO COMPANY

THIS DOCUMENT CONTAINS PROPRIETARY, CONFIDENTIAL, COPYRIGHTED, AND TRADE SECRET INFORMATION OF THE NOCO COMPANIES ("NOCO"). ALL MATERIAL, INFORMATION, AND CONTENT ARE THE PROPERTY OF NOCO, AND NOCO RETAINS ALL RIGHT, TITLE, AND INTEREST THEREIN. THIS DOCUMENT MAY NOT BE COPIED, DISSEMINATED, DISCLOSED, PUBLISHED, DIVULGED, OR REPRODUCED, IN WHOLE OR IN PART, WITHOUT THE PRIOR WRITTEN CONSENT OF NOCO. TITLE IN AND TO THIS DOCUMENT (NO MATTER IF IN PRINTED, ELECTRONIC, OR ANY OTHER FORM) AND ALL INFORMATION CONTAINED HEREIN REMAINS AT ALL TIMES IN NOCO. NO INTELLECTUAL PROPERTY RIGHTS ARE TRANSFERRED TO YOU BY ACCESS TO THIS DOCUMENT OR OTHERWISE. V10.07.19A 23