

BATTERY MASTER SWITCHES

SINGLE PACK

M750

4 POSITION BATTERY SELECTOR SWITCH SURFACE MOUNT

- Continuous/peak 5 sec rating: 310A/500A, SPST
- Material: Thermoplastic, silver contacts
- Battery: 2 x 3/8" - 24 studs
- Function: Battery 1 / 2 / 1+ 2 / Off
- Operating temperature: -40°C to +50°C
- Dimensions: 67 (W) x 67 (L) x 75 (H)mm



LV5015

PANEL MOUNT BATTERY MASTER SWITCH ON/OFF REMOVABLE ACTUATOR

- Voltage: up to 50Vdc
- On - off switch with removable actuator in off position
- Material: Black nylon housing reinforced with fibreglass
- PBT red actuator with battery symbol
- Current rating: 50A max cont., 75A Intermittent
- Insulation resistance: 500Vdc 100MOhm min.
- Dielectric strength: 2000Vdc for 1 min.
- Cranking: 300A for 5 sec.
- Contact resistance: 50 MOhm max
- Cut out hole: Ø22.2mm



LV5043

SURFACE MOUNT BATTERY MASTER SWITCH ON/OFF

- Continuous/peak 5 sec rating: 300A/1000A, DPST
- Material: Thermoplastic, silver contacts
- Battery: 2 x 3/8" - 24 studs
- Operating temperature: -40°C to +50°C
- Dimensions: 67 (W) x 67 (L) x 75 (H)mm



LV5044

4 POSITION BATTERY MASTER SWITCH SURFACE MOUNT

- Continuous/peak 5 sec rating: 300A/1000A, DPST
- Material: Thermoplastic, silver contacts
- Battery: 3 x 3/8" - 24 studs
- Operating temperature: -40°C to +50°C
- Function: Battery 1 / 2 / 1+ 2 / Off
- Dimensions: 67 (W) x 67 (L) x 75 (H)mm



61082BL

SURFACE MOUNT BATTERY ISOLATION SWITCH ON/OFF

- 1500A at 12V for 10 sec.
- 750A at 24V for 10 sec.
- 300A at 12V continuous load max.
- 150A at 24V continuous load max.
- Suitable for applications up to 48V
- Brass terminals & heavy-duty plastic construction
- Dimensions: 67 (W) x 67 (L) x 71 (H)mm

