

Product Release

13 June 2021

24V 3000A

GB251+



COMMERCIAL-GRADE LITHIUM JUMP STARTER.







Product Release

13 June 2021

NOCO BOOST MAX O



INTERFACE

POWER LED

The charger is in standby or the battery voltage is too low for the charger to detect.



ERROR

Illuminates Red if reverse polarity is detected. Blinks "on" and "off" in various sequences (from 1 to 6 blinks) to convey error conditions.



HOT/COLD INDICATOR

Illuminates solid or flashes blue when internal temperature is too low. Illuminates solid or flashes red when internal temperature is too high.



CHARGE LED

Indicates the charge level of the internal battery.



USB RECHARGE. parge virtually any USB device, including smartph

Charge virtually any USB device, including smartphones and tablets. Remote power for a wide range of 12V devices including tire pumps, inverters, lights, phone chargers and more.

BOOST LED

Illuminates white when boost is active.
The LED flashes white when manual override feature is active.



VOLTMETER


Built-in voltmeter displays the voltage of the vehicle's battery for enhanced diagnostics and troubleshooting.




RECHARGE TIME: 8.5hr

From 0-100% 4X Faster. Charge directly from the vehicle's 12-volt auxiliary port or the XGC4 4-Amp Power Adapter to recharge it's 133 watt-hours lithium-ion battery in 8.5 hours.

WHAT'S IN THE BOX





*Accessories not to scale with GB251











12V

XGC-4 Adap

User Guide



EVA Case

TECHNICAL SPECIFICATIONS

INTERNAL Battery:	133 Wh Lithium Ion
PEAK CURRENT RATING:	3000A
OPERATING TEMPERATURE:	-20°C to +50°C
CHARGING TEMPERATURE:	0°C to +40°C
12V (INPUT):	12V/5A (14V Max)
12V (OUTPUT):	12V, 15A Max
USB (OUTPUT):	5V, 2.1A Max Each
HOUSING Protection:	IP65 (w/Ports Closed)
COOLING:	Natural Convection
WEIGHT:	6.17kg