


LJC SERIES FUSIBLE LINK LOW PROFILE J-CASE

- Voltage: up to 58Vdc
- Breaking capacity: 1000A@58Vdc
- Slow blow
- Operating temperature: -40°C to 125°C
- Terminal: Copper alloy
- Plastic body
- Complies with ISO 8820-4 / GB/T31465.4



PACK OF 1/10



PRODUCT INFORMATION


Single Pack	10 Pack	Amperage	Housing Colour	10 Pack	50 Pack	Amperage	Housing Colour
LV5484	LV5484/10	20A	Blue	LV5487	LV5487/10	40A	Green
LV5485	LV5485/10	25A	White	LV5488	LV5488/10	50A	Red
LV5486	LV5486/10	30A	Pink	LV5489	LV5489/10	60A	Yellow

MICRO MJC SERIES FUSIBLE LINK UNSLOTTED M-CASE

- Voltage: up to 32Vdc
- Breaking capacity: 1000A@32Vdc
- Slow blow
- Operating temperature: -40°C to 125°C
- Terminal: Copper alloy
- Plastic body



SINGLE PACK



PRODUCT INFORMATION


Single Pack	Amperage	Housing Colour	Single Pack	Amperage	Housing Colour
LV5495	15A	Grey	LV5498	30A	Pink
LV5496	20A	Light Blue	LV5499	40A	Green
LV5497	25A	White			

FEMALE LARGE FUSIBLE LINK

- Voltage: up to 32Vdc
- Breaking capacity: 1000A@32Vdc
- Slow blow
- Operating temperature: -40°C to 125°C
- Terminal: Copper alloy
- Plastic/ceramic body
- Complies with ISO 8820-4 / GB/T31465.4



SINGLE PACK



PRODUCT INFORMATION

Single Pack	Amperage	Housing Colour	Single Pack	Amperage	Housing Colour
LV5530	20A	Light Blue	LV5534	60A	Yellow
LV5531	30A	Pink	LV5535	70A	Brown
LV5532	40A	Green	LV5536	80A	Black
LV5533	50A	Red	LV5537	100A	Blue