

LED DRL Lamps

BR150DRL SERIES



FEATURES

- Three function LED indicator/park/DRL front bullbar lamp
- Multi-volt 10-30V input & low current draw
- 100,000 hour LED life span with solid state technology
- Maintenance free
- Sealed polycarbonate lens
- Water, dust, vibration & shock proof
- Pre-wired with 300mm sheathed copper cable
- Flush mounted with rubber grommet
- ADR/ECE approved for all functions



ROADVISION's latest generation front bullbar lamps have arrived... Introducing Roadvision's BR150DRL, fully ADR approved three function front indicator, park and now with additional DRL combination bullbar lamps. The BR150DRL delivers the durability of maintenance free LED technology and greater visibility, providing increased safety. With multi-volt input, extremely low current draw, virtually unbreakable polycarbonate lenses, maintenance free, 100,000hr rated lifespan and full ADR approval, the BR150DRL has it all. With ROADVISION it's FIT and FORGET.

PART NUMBERS



BR150DRL

Front Indicator/Park/DRL lamp LED 10-30V 159x49mm Rect Recessed Bull Bar Mount



SPECIFICATIONS

BR150DRL

Current Draw Amps @ 13.8V DC (I/P/DRL)	0.2A/0.03A/0.3A @ 13.8V
Dimensions LxWxH	159x49x33mm
Mounting Depth	Recessed Grommet Mount
Mounting Hole Cut Out	150x40mm
Lamp Functions	Front White Park/DRL/Front Amber Indicator
Indicator Number of LED's	Park - 8 LED's, Indicator - 8 LED's, DRL - 8 LED's
Cable Length	300mm Sheathed Tinned Copper
Approvals	Ind - ECE E4-6R-0125390 Park - ECE E4-77R-0025390 DRL - ECE E4-87R-0025390



DRL Illuminated



Indicator Illuminated



Indicator/Park Light Illuminated



Park Light Illuminated

SPARE PARTS & ACCESSORIES



BR12
LED Load Resistor 12V



BR24
LED Load Resistor 24V

LINE DIAGRAM

