


INSULATION TAPE

Self-Amalgamating Loom Tape

HMAT85

Polyethylene self-amalgamating loom tape ideal for waterproof sealing of electrical connections, temporary repair and sealing of plumbing joints. Also suitable for emergency repair of radiators, engine hoses and auto electrics. Easy to unwind and resistant to water, ozone, UV and a wide range of chemicals including alkalis, hydraulic fluids and vegetable oils.

Voltage	34kV/mm
Elongation	600%
Temperature Range	-35°C to +130°C
Size	Tape Thickness 0.5mm – tensile strength at break 12N/cm.



PVC Electrical Insulation Tape - Black, 10m

8320

PVC Electrical Insulation Tape - Black, 20m

8322

Flame-retardant PVC Electrical Insulation Tape, complying with British standards BS3924 31/90Tp, BS3J10, BS3887 (1985) Part 2 Category 1 and IEC 454-3-1.

Voltage	8.0kV (1 minute proof test 6.0kV)
Conductivity	Less than 2m S/m.
Insulation Resistance	107 megohms
Electrical Properties	Rapid Breakdown
Size	Tape Thickness 0.145mm, tensile-strength at break 26 N/cm.



PVC Electrical Insulation Tape - Red, 10m

8321

PVC Electrical Insulation Tape - Red, 20m

8323

Flame-retardant PVC Electrical Insulation Tape, complying with British standards BS3924 31/90Tp, BS3J10, BS3887 (1985) Part 2 Category 1 and IEC 454-3-1.

Voltage	8.0kV (1 minute proof test 6.0kV)
Conductivity	Less than 2m S/m.
Insulation Resistance	107 megohms
Electrical Properties	Rapid Breakdown
Size	Tape Thickness 0.145mm, tensile-strength at break 26 N/cm.

