

## HEAVY DUTY TRAILER CONNECTORS

SINGLE PACK

### LV2926

#### 2 WAY AUXILIARY DUAL POLE PLUG



- Zinc alloy die-cast housing
- Current rating: 200A
- Brass contacts
- Operating temperature: -30°C to 110°C
- Comes with cable spring
- Approval: SAE J560
- Heavy duty applications



### LV2927

#### 2 WAY AUXILIARY DUAL POLE SOCKET



- Zinc alloy die-cast housing
- Current rating: 200A
- Brass contacts
- Operating temperature: -30°C to 110°C
- Comes with rubber boot
- Approval: SAE J560
- Heavy duty applications



### 15-336S

#### 2 WAY AUXILIARY DUAL POLE PLUG



- Reinforced zinc die-cast housing
- Current rating: 200A
- Nickel plated brass contacts
- Operating temperature: -30°C to 110°C
- Comes with cable spring
- Approval: ISO11446
- Heavy duty applications



### 15-326S

#### 2 WAY AUXILIARY DUAL POLE SOCKET



- Zinc alloy die-cast housing
- Current rating: 200A
- Nickel plated brass contacts
- Operating temperature: -30°C to 110°C
- Comes with rubber boot
- Approval: ISO11446
- Heavy duty applications



### 16-730S

#### HEAVY DUTY TRAILER PLUG 7 PIN ROUND PLASTIC



- Material: Thermoplastic non corrosive
- Brass contacts
- Operating temperature: -30°C to 110°C
- Cable size: 6mm<sup>2</sup>
- ADR approved
- UV resistant



### 16-720S

#### HEAVY DUTY TRAILER SOCKET 7 PIN ROUND PLASTIC



- Material: Thermoplastic non corrosive
- Brass contacts
- Operating temperature: -30°C to 110°C
- Cable size: 6mm<sup>2</sup>
- ADR approved
- UV resistant

