

SHUTDOWN SOLENOIDS

SINGLE PACK/KIT

Baxters
THE DRIVING FORCE IN AUTOMOTIVE SOLUTIONS

BSS149212

12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Copper contact
- Termination: 6.3mm blade terminal
- Mounting bracket: Side mount
- Mounting hole Ø: 2 x 7.4mm elongated
- Applications: Various Kubota models
- Reference: 052600-4530; 16851-60014



BSS1751-24

24V ENGINE SHUTDOWN SOLENOID



- Voltage: 24V
- Material: Metal housing
- Coil terminals: 3 x screw terminals
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 25A, hold current: 0.5A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 50.8mm
- Reference: 1751-24E2U1B1S1A



BSSK3765-12

12V RSV SHUTDOWN SOLENOID KIT
LEFT HAND MOUNT



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 2 x screw terminals
- Bolt left hand mounting
- Rated stroke: 38.6mm (1.5")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Application: RSV Bosch
- Reference: SA-3765-12



BSS1751ES-12

12V ENGINE SHUTDOWN SOLENOID



- Voltage: 12V
- Material: Metal housing
- Coil terminals: 3 x prewired leads
- 2 Bolt mounting bracket
- Rated stroke: 25.4mm (1")
- Pull current: 46A, hold current: 1.1A
- Pull rating: 24 Lbs, hold rating: 38 Lbs
- Operating temperature: -40°C to +120°C
- Cnt to cnt: 63.5mm
- Reference: 1751ES-12E2ULB1S1, SA-3499-12

