

12V 220Ah Slimline Battery with SmartSense DC-DC Charger

The REMCO XTRA series with SmartSense has an ingenious way of working with Smart Alternators. Simply plug your start battery connection directly into the DC input Blue Anderson Plug and charging is optimised to work straight out of the box. For those who want to configure an ignition trigger input, or more sophisticated charging set-ups, the battery has these options available on the two variable switch settings on the battery.

Constructed using hard case metal lithium iron phosphate cells, the battery has an inbuilt Battery Management System (BMS) designed and developed in Australia. Providing up to 240A of continuous discharge and accepting up to 240A of charge, the battery is ready to power your high amperage appliances. The strong aluminium outer enclosure delivers a safe, lightweight and powerful unit which is the perfect building block for next generation battery systems.

At just 24 kg, the unique slimline shape makes it the perfect battery for installations where space is a premium. Slide it behind a seat, under a tray, or against the wall in a custom canopy.

RM12-220LFPXSLSS

Chemistry LiFePO₄
Nominal Voltage 12.0 V
Nominal Capacity 220 Ah
Nominal Energy 2.7 kWh

Input Charge Voltage 13.8 V - 14.6 V

14.0 V recommended

100% SoC Voltage 13.8 V

Low Voltage cut-off 10.5 V approx Charge Current 240 A max Discharge Current 240 A max cont.

480 A surge

Operating Temp. See overleaf

Weight 24.0 kg

Packaged Weight
Life at 80% DoD
Life at 50% DoD
Parallel Capable
Series Capable

24.8 kg approx.
2000 cycles
5000 cycles
Yes (Unlimited)
Yes (Max. 2 in series)

W 257 mmD 90 mmL₁ 672 mm

 $L_2 \qquad \qquad 682 \ mm \ {}_{\text{(inc. terminals/handles)}}$

FEATURES

Size

- ✓ Strong, compact aluminium enclosure
- ✓ Internal BMS
- ✓ Over/Under voltage protection
- ✓ Overcurrent protection
- ✓ Short circuit protection
- ✓ Parallel connect capable
- ✓ Integrated DC-DC Charger with SmartStart: 40 A, 10 V-16 V
- ✓ M8 Threaded Hole Terminals
- √ 1x Grey Anderson (50A Input/Output)
- √ 1x Blue Anderson (DC-DC Input)
- ✓ Battery On/Off Switch
- Designed and fully assembled in Australia












12V 220Ah Slimline Battery with SmartSense DC-DC Charger

TEMPERATURE NOTICE



At temperatures above 60°C, the battery must **NOT** be **operated** (charge or loads). Please move the battery into a cooler environment.

At temperatures above 45°C, the battery must **NOT** be **charged**. Battery lifespan is reduced in these conditions.

Maintain your battery within this range for optimum battery lifespan and performance.

At temperatures below 0°C, the battery must **NOT** be **charged**. Battery performance is reduced in these conditions.

At temperatures below -20°C, the battery must **NOT** be **operated** (charge or loads). Please move the battery into a warmer environment.

INCLUSIONS

Mounting bracket kit

WIREFRAME DIAGRAM

