

INTERMITTENT DUTY SOLENOIDS

SINGLE PACK



24037BX

12V 100A INTERMITTENT DUTY
SOLENOID N/O CONTACTS



- Continuous Rating: 100A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"- 24)
- Coil studs: 1 x stud terminals (10 - 32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm




24008BX

24V 120A INTERMITTENT DUTY
SOLENOID N/O CONTACTS



- Continuous Rating: 120A, SPST
- Material: Plated steel case
- Contacts: Copper
- Battery Studs: 2 x copper stud (5/16"- 24)
- Coil studs: 2 x stud terminals (10 - 32)
- Operating temperature: -40°C to +85°C, insulated ground
- Cnt to cnt: 56mm
- Dimensions: 46.5 x 64 x 84mm




24450BX

12V 75A MOTOR REVERSING
SOLENOID



- Intermittent duty: 75A, DPST
- Material: Glass nylon housing
- Contacts: Copper
- Battery studs: 4 x copper stud (5/16"-24)
- Coil studs: 2 x blade terminals
- Operating temperature: -40°C to +60°C, insulated ground
- Cnt to cnt: 105mm
- Dimensions: 76.5 x 83 x 127mm

Note: Forward, Reversing Function



24450-02BX

24V 45A MOTOR REVERSING
SOLENOID



- Intermittent duty: 45A, DPST
- Material: Glass nylon housing
- Contacts: Copper
- Battery studs: 4 x copper stud (5/16"-24)
- Coil studs: 2 x blade terminals
- Operating temperature: -40°C to +60°C, insulated ground
- Cnt to cnt: 105mm
- Dimensions: 76.5 x 83 x 127mm

Note: Forward, Reversing Function

