

SINGLE PACK

CTEK
MAXIMIZING BATTERY PERFORMANCE

40-100

12/24V 40/20A MXTS 40 BATTERY CHARGER & POWER SUPPLY

- Current: 40A (12V), 20A (24V)
- Voltages: 12V, 24V
- Chemistry: Lead acid
- Types: WET, MF, CA, AGM, GEL
- Battery Capacity Range: 12V up to 1200Ah, 24V up to 600Ah
- Operating temperature: -20°C to +50°C
- Dimensions: 254 x 160 x 76mm
- Weight: 1.3kg
- 2 Years warranty

Comes with:

- Clamps
- User Guide



40-015

12/24V 50A MXTS 70/50 BATTERY CHARGER & POWER SUPPLY

- Current: 50A DC
- Voltages: 12V, 24V
- Chemistry: Lead acid
- Types: WET, MF, CA, AGM, GEL
- Battery Capacity Range: 20-1500Ah
- Operating temperature: -20°C to +50°C
- Dimensions: 380 x 300 x 220mm
- Weight: 8.5kg
- 2 Years warranty

Comes with:

- Clamps
- User Guide



56-767

24V 14A MXT 14 BATTERY CHARGER & POWER SUPPLY

- Current: 14A DC
- Voltages: 24V
- Chemistry: Lead acid
- Types: WET, MF, CA, AGM, GEL
- Battery Capacity Range: 28-500Ah
- Operating temperature: -20°C to +50°C
- Dimensions: 235 x 130 x 65mm
- Weight: 1.9kg
- 2 Years warranty

Comes with:

- Clamps
- User Guide

