


HEATSHRINK IN SPOOL

- Material: Polyolefin
- Ratio: 2:1
- Max. rating: 300V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in spool



SPOOL



PRODUCT INFORMATION

Part No.	Inside Dia.	Colour	Length
LV3301	3mm	Black	400m
LV3303	3mm	Red	400m
LV3305	5mm	Black	200m
LV3307	5mm	Red	200m
LV3309	7mm	Black	100m
LV3311	7mm	Red	100m
LV3313	10mm	Black	100m

Part No.	Inside Dia.	Colour	Length
LV3315	10mm	Red	100m
LV3317	13mm	Black	100m
LV3319	13mm	Red	100m
LV3321	19mm	Black	100m
LV3323	19mm	Red	100m
LV3325	25mm	Black	50m
LV3327	25mm	Red	50m

HEATSHRINK IN DISPENSER BOX

- Material: Polyolefin
- Ratio: 2:1
- Max. rating: 300V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in dispenser box



DISPENSER BOX



PRODUCT INFORMATION

Part No.	Inside Dia.	Colour	Length
LV3330	3mm	Black	15m
LV3331	3mm	Red	15m
LV3332	5mm	Black	12m
LV3333	5mm	Red	12m
LV3334	7mm	Black	10m
LV3335	7mm	Red	10m
LV3336	10mm	Black	10m
LV3337	10mm	Red	10m

Part No.	Inside Dia.	Colour	Length
LV3338	13mm	Black	8m
LV3339	13mm	Red	8m
LV3340	16mm	Black	5m
LV3341	16mm	Red	5m
LV3342	19mm	Black	5m
LV3343	19mm	Red	5m
LV3344	25mm	Black	4m
LV3345	25mm	Red	4m