

SINGLE PACK

THE POWER OF
REDARC

SRP0120

10A 12/24VDC PWM SOLAR CHARGE CONTROLLER

- Battery voltage: 12/24V
- Max. PV open circuit voltage: 30V/55V
- Rated charge current: 10A
- Operating temperature: -35°C to +50°C
- Dimensions: 153 x 76 x 37mm



SRP0240

20A 12/24VDC PWM SOLAR CHARGE CONTROLLER

- Battery voltage: 12/24V
- Max. PV open circuit voltage: 30V/55V
- Rated charge current: 20A
- Operating temperature: -35°C to +50°C
- Dimensions: 153 x 76 x 37mm



SRPA0240

20A 12/24VDC PWM SOLAR CHARGE CONTROLLER WITH ANDERSON PLUGS

- Battery voltage: 12/24V
- Max. PV open circuit voltage: 32V/50V
- Rated charge current: 20A
- Operating temperature: -35°C to 55°C
- Dimensions: 103 x 153 x 28mm



SRPA0360

30A 12/24VDC PWM SOLAR CHARGE CONTROLLER WITH ANDERSON PLUGS

- Battery voltage: 12/24V
- Max. PV open circuit voltage: 32V/50V
- Rated charge current: 30A
- Operating temperature: -35°C to 55°C
- Dimensions: 108 x 153 x 28mm

