

RELAY CONNECTORS

**4973**

Relay Connector

4973BULK

Relay Connector (Pack of 30)

Sturdy plastic casing. Supplied with 5 blade terminals.

Mounting Single screw mounting

Suits 4 and 5 pin relays with 6.3mm and 2.8mm flat pin connectors.
HELLA Part Nos 3076, 3077, 3078, 3079, 3080, 3081

Note Part No. 3076 and 3077 are not suitable for multiple installation using this connector.

WEATHER PROOF CHANGEOVER RELAYS

NEW**HMWPR001**

Weatherproof Relay and Connector Assembly Kit, 12V

HMWPR002

Weatherproof Relay and Connector Assembly Kit, 24V

12V ISO mini relay and connector assembly kit contains:

1 x ISO-style 12 volt changeover relay.

1 x Connector body with seals for pull to seat terminals.

3 x Large barrel pull to seat terminal 6.3mm width suits cable size 3.00mm².

2 x Small barrel pull to seat terminal 6.3mm width suits cable size 1.00 - 2.00mm²

Transient Suppressor Resistor: 680 Ohms.

Voltage 10 -16V DC

Operating Range -40°C to +125°C

Contact Current Rating NO 35A / NC 20A

Coil Resistance 70-90 Ohms @ 23°C

Transient Suppressor Resistor 680 Ohms

Pin & Wiring

