

PVC HARNESS TAPE

- Weather resistant
- Material: PVC
- Thickness: 0.11mm
- Rubber based adhesive
- Weather resistance
- Flame retardant
- Elongation@break: 203%
- Operating temperature: 80°C max.
- Voltage: 600V max.



Nitto

PACK OF 10



PRODUCT INFORMATION

Part No.	Colour	Width	Length	Qty	Replaces
LV3157	Black	19mm	20m	10	E60-2100

AMALGAMATING/SELF FUSING TAPE

- Flame retardant
- Non-vulcanized butyl rubber tape
- Non corrosive to metal
- Flame retardant
- Thickness: 0.5mm
- Rubber based adhesive
- Elongation@break: 550%
- Operating temperature: 80°C max.
- Voltage: 6 - 22kV



Nitto

SINGLE PACK



PRODUCT INFORMATION

Part No.	Colour	Width	Length	Qty	Replaces
LV3158	Black	19mm	10m	1	E60-2115

PET CLOTH TAPE

- Backing material: PET cloth
- Advanced acrylic adhesive
- High abrasion protection
- Flame retardant
- Designed for engine compartment
- Thickness: 0.26mm
- Elongation@break: 40%
- Operating temperature: -40°C to 150°C



tesa

SINGLE PACK



PRODUCT INFORMATION

Part No.	Colour	Width	Length	Qty
LV3161	Black	19mm	25m	1

PET FLEECE TAPE

- Backing material: PET fleece
- Rubber based adhesive
- Abrasion resistant
- Flame retardant
- Hand tearable
- Noise dampening
- Designed for in cabin use
- Thickness: 0.28mm
- Elongation@break: 20%
- Operating temperature: -40°C to 105°C



tesa

SINGLE PACK



PRODUCT INFORMATION

Part No.	Colour	Width	Length	Qty
LV3162	Black	19mm	25m	1