

Product Release

DENSO TAPE

ALL PURPOSE PETROLATUM TAPE

Denso Tape is composed of a non-woven synthetic fabric carrier, fully impregnated with a neutral compound based on saturated petrolatum and inert siliceous fillers.

Denso Tapes are designed to withstand extreme temperature variations. The tapes provide long term corrosion protection to pipes, flanges, valves and related surfaces.

Features:

- Meets NACE RP0375-2006
- Applied to marginally prepared surfaces (SSPC SP 2-3)
- Conforms to irregular shapes and profiles
- Can be applied to cold, wet surfaces
- Not effected by water, acid, salts or soil organics
- Encapsulation of lead paint
- Contains no solvents
- Easy application from arctic to tropical temperatures
- Ready for immediate service after application
- Meets AS 4822-2008, ISO 21809-3:2008 and AWWA C217 Standard
- Over an 80 year history of proven applications

Specifications:

Properties:	Values
Thickness (ASTM D1000):	1.15 mm avg.
Weight:	1.44 kg/m ² avg.
Breaking Strength (ASTM D1000):	200 N/50 mm min.
Elongation @ Break:	10% avg.
Breakdown Voltage (55% overlap):	16 kV min.
Resistance to Acids, Alkalies and Salts:	Excellent
Maximum Service Temperature:	70°C
Roll Widths:	50 / 75 / 100mm
Roll Length:	10m



PRODUCT INFORMATION

Part No.	Description	Barcode
LV3165	50mm x 10m	9342828200745
LV3166	75mm x 10m	9342828200752
LV3167	100mm x 10m	9342828200769