

Product Release



DENSYL TAPE KF GREY HIGH TEMPERATURE PETROLATUM TAPE

Densyl Tape is composed of a non-woven synthetic fabric carrier, fully impregnated with a neutral compound based on saturated petrolatum and inert siliceous fillers.

Densyl Tapes are designed to withstand extreme temperature variations. The tapes provide long term corrosion protection to pipes, flanges, valves and related surfaces.

Features:

- Meets NACE RP0375-2006
- Applied to marginally prepared surfaces (SSPC SP 2-3)
- Conforms to irregular shapes and profiles
- Can be applied to cold, wet surfaces
- Not effected by water, acid, salts or soil organics
- Encapsulation of lead paint
- Contains no solvents
- Easy application from arctic to tropical temperatures
- Ready for immediate service after application
- Meets AS 4822-2008, ISO 21809-3:2008 and AWWA C217 Standard
- Over an 80 year history of proven applications

Specifications:

Properties:	Values
Thickness (ASTM D1000):	1.15 mm avg.
Weight:	1.44 kg/m 2 avg.
Breaking Strength (ASTM D1000):	200 N/50 mm min.
Elongation @ Break:	10% avg.
Breakdown Voltage (55% overlap):	16 kV min.
Resistance to Acids, Alkalies and Salts:	Excellent
Maximum Service Temperature:	70°C
Roll Widths:	50 / 100mm
Roll Length:	8m
Recommended Primer:	Denso Hi-Tack Primer



PRODUCT INFORMATION

Part No.	Description	Barcode
LV3168	50mm x 8m	9342828203050
LV3169	100mm x 8m	9342828203067