

DUAL WALL HEATSHRINK IN DISPENSER BOX

- Material: Polyolefin
- Ratio: 3:1
- Breakdown voltage: 600V
- Operating temperature: -55°C to +125°C
- UL VW-1 & CSA: flame retardant, self extinguishing
- Pack in dispenser box



DISPENSER BOX



PRODUCT INFORMATION

Part No.	Inside Dia.	Colour	Length	Part No.	Inside Dia.	Colour	Length
LV3385B	3.2mm	Black	15m	LV3388R	9.5mm	Red	6m
LV3385R	3.2mm	Red	15m	LV3389B	12.7mm	Black	5m
LV3386B	4.8mm	Black	10m	LV3389R	12.7mm	Red	5m
LV3386R	4.8mm	Red	10m	LV3390B	19.1mm	Black	3m
LV3387B	6.4mm	Black	7m	LV3390R	19.1mm	Red	3m
LV3387R	6.4mm	Red	7m	LV3391B	25.4mm	Black	3m
LV3388B	9.5mm	Black	6m	LV3391R	25.4mm	Red	3m

LV3358

DUAL HEATSHRINK ASSORTMENT KIT

- 88 pieces
- Material: Polyolefin
- Ratio: 3:1
- Waterproof
- Adhesive lined inner wall seals & protects against moisture ingress preventing corrosion
- Quick & simple to shrink by heat gun
- Protection & insulation of components & wires
- Plastic storage case



88 PIECES



KIT CONTAINS

Inside Dia.	Colour	Length	Qty	Inside Dia.	Colour	Length	Qty
3.2mm	Black	50mm	15	7.9mm	Red	50mm	4
3.2mm	Red	50mm	15	9.5mm	Black	50mm	3
4.8mm	Black	50mm	10	9.5mm	Red	50mm	3
4.8mm	Red	50mm	10	12.7mm	Black	50mm	3
6.4mm	Black	50mm	6	12.7mm	Red	50mm	3
6.4mm	Red	50mm	6	19.1mm	Black	50mm	3
7.9mm	Black	50mm	4	19.1mm	Red	50mm	3