

FLUSH MOUNT SOCKETS & GAUGES

SINGLE PACK



LV1832

FLUSH MOUNT TWIN OUTPUT USB PORT
QUICK CHARGE WITH C TYPE PORT



- Voltage: 12/24V
- Housing material: Thermoplastic Nylon 66
- Port 1 output: 3.6 - 12V/QC3.0A
- Port 2 output: 5.0 - 20V/QC4.0A
- Port 2: C-Type
- Blue LED illumination
- Operating temperature: -40°C - 85°C
- Hole size: Ø26mm



LV1835

FLUSH MOUNT TWIN OUTPUT USB PORT
FAST CHARGE/QUICK CHARGE



- Voltage: 12/24V
- Housing material: Thermoplastic Nylon 66
- Port 1 output: 5V/2.4A
- Port 2 output: 3.6 - 12V/QC3.0A
- Terminals: Push on (2 x 6.3mm)
- Blue LED illumination
- Operating temperature: -40°C - 85°C
- Hole size: Ø26mm: push on (2 x 6.3mm)



LV1838

FLUSH MOUNT TWIN OUTPUT USB PORT
QUICK CHARGE & VOLTAGE DISPLAY



- Voltage: 12/24V
- Housing material: Thermoplastic Nylon 66
- Output: 3.6V - 12V/QC3.0A x 2
- 12V Voltmeter with On/Off switch
- Voltage display range: 11 - 14.6V
- Blue LED illumination
- Operating temperature: -40°C - 85°C
- Hole size: Ø26mm



LV1840

FLUSH MOUNT TWIN OUTPUT USB PORT
QUICK CHARGE PD-60W



- Voltage: 12/24V
- Housing material: Thermoplastic Nylon 66
- Output: QC4.0A x 2 PD-60W
- Blue LED illumination
- Operating temperature: -40°C - 85°C
- Hole size: Ø29mm



LV1839

FLUSH MOUNT UHF RADIO PORT

- Housing material: Thermoplastic Nylon 66
- Universal RJ45 adaptor
- Connects UHF CB radios
- Panel thickness: >2mm
- O/H length: 43mm
- Depth: 37.5mm
- Hole: Ø29mm



LV1742

TWIN USB ADAPTOR PLUG
WITH LED DISPLAY



- Voltage: 12/24V
- USB output: 5V/2.4A per port
- Displays voltage with no load
- Displays current draw with load
- Material: ABS & PC fireproof shell

