LED Beacons



FEATURES

- 360° high intensity LED beacon
- Available in quad strobe or simulated rotating
- Multi-volt 10-36V input & low current draw
- 30 SMD LED's producing 10 watts
- Brighter than conventional incandescent systems
- 100,000 hour rated LED life span
- Tough polycarbonate lens and housing
- Vibration and waterproof sealed unit
- Available in 3 hole fixed or magnetic mounts















Roadvision's RB130 series compact LED 360° strobe or rotating beacons... perfect for everyday use and abuse! Roadvision's super bright RB130 Series compact strobe or simulated rotating beacons deliver the durability of maintenance free LED technology and greater visibility, providing increased safety. Featuring multi-voltage 10-36V input, high impact polycarbonate lens and housing, they offer superior construction quality and extreme durability. The RB130's 30 high performance SMD LED's produce 10 watts whilst drawing only 0.7 amps, making it an ideal solution where voltage drop is an issue. Available in quad flash or simulated rotating patterns with 3 bolt fixed or magnetic mounts, these beacons are weatherproof and maintenance free with a life span rated at 100,000 hours. With ROADVISION it's FIT and FORGET.

PART NUMBERS



RB130YBeacon LED 10-36V Quad Strobe Amber Fixed Mount











RB130YR
Beacon LED 10-36V Simulated Rotating Amber Fixed Mount











RB130MYBeacon LED 10-36V Quad Strobe Amber Magnetic Mount











RB130MYR
Beacon LED 10-36V Simulated Rotating Amber Magnetic Mount









SIMULATED ROTATING BEACONS

Simulated Rotating is the term referred to, where the beacons LED's illuminate in a chaser pattern rather than a flashing strobe pattern. The rows of LED's illuminate one after the other at a speed of 180rpm creating the illusion that the internal light source is rotating inside the lens like a standard beacon.









SPECIFICATIONS

	RB130Y	RB130YR	RB130MY	RB130MYR
Function	Quad Strobe	Simulated Rotating	Quad Strobe	Simulated Rotating
Light Source	30 SMD LED's	30 SMD LED's	30 SMD LED's	30 SMD LED's
Flash / Rotation Rate	Quad	180rpm	Quad	180rpm
Dimensions	117.3x130mm	117.3x130mm	117.3x130mm	117.3x130mm
Current Draw Amps	0.7A @ 13.8V	0.7A @ 13.8V	0.7A @ 13.8V	0.7A @ 13.8V
Mounting Type	3 Hole Fixed 118mm C/C	3 Hole Fixed 118mm C/C	Magnetic	Magnetic
Wiring	350mm Pre-Wired	350mm Pre-Wired	3m Curly Cord with Cig. Plug	3m Curly Cord with Cig. Plug

LINE DIAGRAM



